

2026 Marin Bobcat Trail 3 - Geometrical Chart



| Geometry | Extra Small | Small | Medium | Large | XLarge |
|---------------------|-------------|-------|--------|-------|--------|
| A Stack | | 603 | 608 | 639 | 644 |
| B Reach | | 445 | 455 | 475 | 495 |
| C Headtube angle | | 66.5° | 66.5° | 66° | 66° |
| D Headtube length | | 105 | 110 | 115 | 120 |
| E Seattube length | | 381 | 431 | 482 | 520 |
| F Seattube angle | | 74.5° | 74.5° | 74.5° | 74.5° |
| G Toptube effective | | 612 | 623 | 652 | 673 |
| H Bb height | | 307 | 307 | 311.5 | 311.5 |
| I Bb drop | | 48 | 48 | 61 | 61 |
| J Chainstay | | 415 | 415 | 430 | 430 |
| K Wheelbase | | 1144 | 1156 | 1208 | 1230 |

| Geometry | Extra Small | Small | Medium | Large | XLarge |
|---------------------|--------------------|--------------|---------------|--------------|---------------|
| L Standover height | | 640 | 690 | 732 | 760 |
| M Fork offset | | 42 | 42 | 46 | 46 |
| N Seatpost diameter | | 30.9 | 30.9 | 30.9 | 30.9 |
| O Handlebar width | | 780 | 780 | 780 | 780 |
| P Stem length | | 45 | 45 | 45 | 45 |
| Q Crank length | | 170 | 170 | 170 | 170 |