

# 2026 Marin RIFT Zone 1 - Specifications

Spec and price beign subject to change without notification

## Frame

Series 3 6061 Aluminum, 27.5 or 29" Wheels, 130mm Travel, MultiTrac Suspension Platform, 148x12mm Boost Thru-Axle, 73mm Threaded BB w/ ISCG05 Tabs

## Front Suspension

X-Fusion Slide (29) or Sweep(27.5) Boost RC, 140mm Travel, Compression and Rebound Adjustment, 44mm Offset

## Rear Suspension

X-Fusion O2 Pro R, Custom Tune, 210x55mm, M8x25mm Hardware Top and Bottom

## Rim

Marin Aluminum Double Wall, 29mm Inner, Pinned Joint, Disc Specific, Tubeless Compatible

## Hub Rear

Shimano HB-MT200B, 141 QR, Centerlock, Standard Freehub Body

## Hub Front

Shimano HF-MT400B, 110x15mm, Centerlock

## Spokes

14g Black Stainless Steel

## Tires

Vee Tire Snap WCE 2.35", Top 40 Compound, GXE Core, 90 TPI, Tubeless compatible

## Derailleur Rear

Shimano RD-U6000, 11-Speed GS

## Shift Lever

Shimano, SL-U6000-11R, 11-Speed

## Crankset

Marin Forged Alloy, Integrated Steel 32T Narrow Wide Chainring, 170mm Crank Length, Boost Spacing

## **Bottom Bracket**

External Sealed Cartridge Bearing

## **Chain**

Shimano LG-500 11-Speed

## **Cassette**

Shimano CS-LG400-11, 11-Speed, 11-50T

## **Brakes Front**

Tektro HD-M280 Hydraulic Disc, 180mm Rotor

## **Brakes Rear**

Tektro HD-M280 Hydraulic Disc, 180mm Rotor

## **Brake Levers**

Tektro HD-M280

## **Handlebar**

Marin Mini-Riser, 6061 Double Butted Aluminum, 780mm Width, 28mm Rise, 5° Up, 9° Back

## **Stem**

Marin 3D Forged Alloy, 35mm

## **Grips**

Marin MTN, Closed End

## **Headset**

FSA No 57E, Semi-Sealed Cartridge Bearings, 1 1/8" x 1 1/2"

## **Seatpost**

X-Fusion Manic, 1x Composite Remote, Size XS-S 150mm Travel, Size M-XL 170mm Travel, 30.9mm

## **Saddle**

Marin Speed Concept