

2026 Marin San Quentin 1 - Specifications

Spec and price beign subject to change without notification

Frame

Series 2 6061 Aluminum 27.5 or 29" Wheel, Double Butted, Internal Cable Routing, 141mm Open Dropout, 73mm Threaded BB

Front Suspension

SR Suntour XCM34 Boost 15x110mm Spacing, 130mm Travel, Coil Spring, 27.5", Bolt-On Thru-Axle

Rim

Marin Aluminum Double Wall, Specific, 29mm Inner, Pinned Joint, 32H, Tubeless Compatible

Hub Rear

Forged Alloy, Quad Sealed Cartridge Bearings, Alloy Axle, QR type, 141mm Width, 32H, Shimano Standard Freehub Body

Hub Front

Forged Alloy, 110x15mm, Sealed Cartridge Bearing, 32H

Spokes

14g Black Stainless Steel

Tires

Delium Vesatile, All-Around Construction, 2.5", Wire-Bead Tubeless

Derailleur Rear

MicroShift RD-M9195M, 9 Speed, With Clutch

Shift Lever

MicroShift SL-M9195-R, 1x9 with Bearings

Crankset

Marin Forged Alloy, Integrated Steel 32t Narrow Wide Changing, Boost Spacing

Bottom Bracket

Sealed Cartridge Bearing, Square Taper

Chain

KMC X-9

Cassette

SunRace, 9 Speed, 11-46T

Brakes Front

Tektro M275 Hydraulic, 180mm Rotor

Brakes Rear

Tektro M275 Hydraulic, 180mm Rotor

Brake Levers

Tektro M275

Handlebar

Marin Mini-Riser, 6061 Double Butted Aluminum, 780mm Width, 28mm Rise, 5° Up, 9° Back

Stem

Marin 3D Forged Alloy, 45mm

Grips

Marin MTN, Closed End

Headset

FSA No 57E, Semi-Sealed Cartridge Bearings, 1 1/8" x 1 1/2"

Seatpost

Marin Alloy, 30.9mm

Saddle

Marin Speed Concept

Pedals

Marin MTB Plastic