

M. Fork Offset	50.0	50.0	50.0	50.0	50.0	50.0
N. Wheelbase	1027.0	1037.0	1049.0	1061.0	1083.0	1115.0
Crank Arm Length	165.0	165.0	170.0	172.5	175.0	175.0
Handlebar Width	38.0	40.0	44.0	44.0	46.0	46.0
Recommended Rider Height	142.0 - 150.0	150.0 - 157.0	157.0 - 168.0	165.0 - 175.0	173.0 - 183.0	183.0 - 193.0
Stem Length	60.0	70.0	80.0	80.0	90.0	100.0

Imperial

Size	49cm	51cm	53cm	55cm	57cm	60cm
A. Effective Top Tube	19.41	20.08	20.87	21.65	22.44	23.62
B. Stand Over	24.65	25.91	27.09	28.46	29.92	31.02
C. Reach	14.41	14.57	14.69	14.84	15.28	16.14
D. Stack	20.08	20.63	21.57	22.28	23.39	24.49
E. Total Seat Tube Length	13.58	14.96	16.14	17.72	19.29	20.47
F. Headtube Length	3.54	4.13	5.12	5.91	7.09	8.27
G. Headtube Angle	68.5	68.5	68.5	68.5	68.5	68.5
H. Seat Tube Angle	76.0	75.0	74.0	73.0	73.0	73.0
I. BB Drop	2.76	2.76	2.76	2.76	2.76	2.76
J. BB Height	11.22	11.22	11.22	11.22	11.22	11.22
K. Chainstay Length	17.32	17.32	17.32	17.32	17.32	17.32
L. Fork Length Axle to Crown	15.83	15.83	15.83	15.83	15.83	15.83
M. Fork Offset	1.97	1.97	1.97	1.97	1.97	1.97
N. Wheelbase	40.43	40.83	41.3	41.77	42.64	43.9
Crank Arm Length	6.5	6.5	6.69	6.79	6.89	6.89
Handlebar Width	149.61	157.48	173.23	173.23	181.1	181.1
Recommended Rider Height	55.91 - 59.06	59.06 - 61.81	61.81 - 66.14	64.96 - 68.9	68.11 - 72.05	72.05 - 75.98
Stem Length	2.36	2.76	3.15	3.15	3.54	3.94

Measurements based on:

- An unsprung bike (no sag)
- A 700c x 42 mm tire measuring 710 mm in diameter
- Standover (B) for all sizes is measured vertically to top of toptube from a position 50 mm forward of BB center