

2026 Salsa Notch Deore 12 - Silver - Build Kit

Build Kit

Frameset

- Frame
Notch Aluminum
- Color
Silver
- Suspension Fork
RockShox Domain Gold RC, 170mm
- Rear Shock
Fox Float X Performance Series

Components

- Headset
ACROS AZX-721 ZS56/ZS66 for 1.8" tapered steerer
- Seatpost
Tranz X YSP18, SM: 150mm travel; MD, LG, XL: 170mm travel
- Stem
Salsa Guide 40mm
- Grips/Bar Tape
WTB Wavelength
- Saddle
WTB Solano, Medium, Fusion Form, steel rail
- Handlebar
RaceFace Chester, 780mm wide, 20mm rise
- Lights Included
No

Drivetrain

- Front Derailleur

N/A

- Rear Derailleur

Shimano Deore M6100-SGS

- Cassette

Shimano Deore M6100-12, 10–51t, 12-speed

- Drive Type

Mid-Drive

- Chain

Shimano Deore M6100 HYPERGLIDE+

- Crankset

FSA CK-762 w/ RaceFace direct-mount chainring, 34t. MRP 1x SL TR2 for Bosch Performance Line CX BDU37

- Shifter

Shimano Deore M6100

- Brake Levers

Shimano Deore M6100

- Brake Calipers

Shimano Deore M6120, 4-piston

- Assist Levels

Eco, Tour, eMTB, Turbo (Bosch smart system offers programable mode settings in the eBike Flow app)

- Rotors

Shimano Deore RT64, Center Lock (220mm front and rear)

- Drive Unit

Bosch Performance Line CX - BDU37

- Ebike Classification

Class 1

- Max Assist Speed

20 mph / 32 km/h

- Motor Torque

85Nm

- Max Motor Assist

340% up to 600 watts

- Battery Capacity Watt Hours

500Wh

- Battery Type

Li-Ion (PowerTube 500)

- Removable Battery

Removable for service

- Battery Power Volts

36V

- Battery Capacity Amp Hours

13.4Ah

- Estimated Charge Time

4.5 hours

- Charger Included

Yes

- Range Estimate

60 miles

- Throttle

No

- Walk Assist

Yes

Wheels

- Front Tire

Teravail Kessel 29 x 2.6", Ultra Durable casing, WTB TCS Sealant included (tubes installed)

- Rear Tire

Teravail Warwick 29 x 2.5", Ultra Durable casing, WTB TCS Sealant included (tubes installed)

- Front Hub

Shimano TC500-15-B, 32h

- Rear Hub

Shimano TC500-MS-B, 32h

- Spoke

2.0 mm straight gauge, black

- Rim

WTB ST i30 Tough, TCS

Weight

- Complete Bike

59 lbs 0 oz (Medium)

*Specifications are subject to change without notice