

| | | | | | | | |
|-------------------------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| L. Fork Length Axle to Crown | 420.0 | 420.0 | 420.0 | 420.0 | 420.0 | 420.0 | 420.0 |
| M. Fork Offset | 51.0 | 51.0 | 51.0 | 51.0 | 51.0 | 51.0 | 51.0 |
| N. Wheelbase | 1017.0-1032.0 | 1027.0-1041.0 | 1037.0-1051.0 | 1053.0-1067.0 | 1069.0-1084.0 | 1085.0-1100.0 | 1101.0-1116.0 |
| Crank Arm Length | 165.0 | 170.0 | 175.0 | 180.0 | 180.0 | 180.0 | 180.0 |
| Handlebar Width | 40.0 | 42.0 | 44.0 | 46.0 | 48.0 | 50.0 | 52.0 |
| Recommended Rider Height | 142.0 - 157.0 | 155.0 - 165.0 | 162.0 - 173.0 | 170.0 - 180.0 | 178.0 - 188.0 | 185.0 - 193.0 | 190.0 |
| Stem Length | 60.0 | 70.0 | 80.0 | 90.0 | 90.0 | 100.0 | 110.0 |

Imperial

| Size | 49cm | 52.5cm | 54.5cm | 56cm | 57.5cm | 59cm | 61cm |
|-------------------------------------|---------------|---------------|---------------|---------------|---------------|---------------|-------------|
| A. Effective Top Tube | 19.92 | 20.75 | 21.46 | 22.05 | 22.64 | 23.23 | 23.82 |
| B. Stand Over | 27.01 | 28.62 | 29.76 | 30.94 | 31.26 | 32.28 | 33.19 |
| C. Reach | 14.41 | 14.61 | 14.69 | 15.04 | 15.43 | 15.79 | 16.18 |
| D. Stack | 20.87 | 21.42 | 22.17 | 22.87 | 23.62 | 24.37 | 25.08 |
| E. Total Seat Tube Length | 15.35 | 17.32 | 18.7 | 20.08 | 20.47 | 21.46 | 22.44 |
| F. Headtube Length | 3.54 | 4.13 | 4.92 | 5.71 | 6.5 | 7.28 | 8.07 |
| G. Headtube Angle | 70.0 | 70.0 | 70.0 | 70.0 | 70.0 | 70.0 | 70.0 |
| H. Seat Tube Angle | 75.25 | 74.0 | 73.0 | 73.0 | 73.0 | 73.0 | 73.1 |
| I. BB Drop | 2.76 | 2.76 | 2.76 | 2.76 | 2.76 | 2.76 | 2.76 |
| J. BB Height | 11.42 | 11.42 | 11.42 | 11.42 | 11.42 | 11.42 | 11.42 |
| K. Chainstay Length | 17.13-17.72 | 17.13-17.72 | 17.13-17.72 | 17.13-17.72 | 17.13-17.72 | 17.13-17.72 | 17.13-17.72 |
| L. Fork Length Axle to Crown | 16.54 | 16.54 | 16.54 | 16.54 | 16.54 | 16.54 | 16.54 |
| M. Fork Offset | 2.01 | 2.01 | 2.01 | 2.01 | 2.01 | 2.01 | 2.01 |
| N. Wheelbase | 40.04-40.63 | 40.43-40.98 | 40.83-41.38 | 41.46-42.01 | 42.09-42.68 | 42.72-43.31 | 43.35-43.94 |
| Crank Arm Length | 6.5 | 6.69 | 6.89 | 7.09 | 7.09 | 7.09 | 7.09 |
| Handlebar Width | 157.48 | 165.35 | 173.23 | 181.1 | 188.98 | 196.85 | 204.72 |
| Recommended Rider Height | 55.91 - 61.81 | 61.02 - 64.96 | 63.78 - 68.11 | 66.93 - 70.87 | 70.08 - 74.02 | 72.83 - 75.98 | 74.8 |
| Stem Length | 2.36 | 2.76 | 3.15 | 3.54 | 3.54 | 3.94 | 4.33 |

Measurements based on:

- a fork measuring 420x51mm
- a 700x42mm tire measuring 720 mm in diameter
- standover (B) measured vertically to top of toptube from a position 50mm forward of BB center.