

# 2026 Santa Cruz Blur X0 AXS Trail RSV - Geometry

## Shock Position - Blur XC

	s	m	l	xl
Reach	425	450	470	495
Stack	578.3	587.6	596.9	610.8
Head tube angle	68.3°	68.3°	68.3°	68.3°
Seat Tube Length	405	430	470	520
Front Center	685.8	714.5	738.2	768.7
BB Height	330.5	330.5	330.5	330.5
BB Drop	42	42	42	42
Wheel base	1115.8	1147	1173.2	1206.2
Rear Center	430	432.5	435	437.5
Headtube length	90	100	110	125
Top Tube Length	563.9	592.8	616.9	647.2
Seat Tube Angle	76.5°	76.3°	75.8°	75.7°
Standover Height	737	740	739	745

## Shock Position - Blur TR

	s	m	l	xl
Reach	412.3	437.8	457.5	482.5
Stack	587.4	597	606.5	620.7
Head tube angle	67.1°	67.1°	67.1°	67.1°
Seat Tube Length	405	430	470	520
Front Center	695	723.7	747.4	778
BB Height	339.9	339.7	339.6	339.4
BB Drop	32.6	32.8	32.9	33.1
Wheel base	1125.8	1157	1183.2	1216.3
Rear Center	430.8	433.3	435.8	438.3
Headtube length	90	100	110	125
Top Tube Length	568.4	597.3	621.4	651.7
Seat Tube Angle	75.1°	75°	74.9°	74.8°
Standover Height	744	746	745	750