



Size	A : Stack	B : Reach	C : Effective Top Tube @75° Seat Tube	D : Effective Top Tube @79° Seat Tube	E : Wheel Size	F : Head Tube Angle	G : Trail *	H : Fork Offset	I : Head Tube Length	J : Bottom Bracket Drop	K : Front Center	L : Wheelbase	M : Standover Height	N : Chainstay Length
48	485 mm (19.09 ")	381 mm (15.00 ")	511 mm (20.12 ")	475 mm (18.70 ")	700c	71°	62.4 mm (2.46 ")	52 mm (2.05 ")	87.5 mm (3.44 ")	75 mm (2.95 ")	582 mm (22.91 ")	975 mm (38.39 ")	732 mm (28.82 ")	405 mm (15.94 ")
51	506 mm (19.92 ")	398 mm (15.67 ")	533 mm (20.98 ")	496 mm (19.53 ")	700c	72.5°	62.4 mm (2.46 ")	43 mm (1.69 ")	101 mm (3.98 ")	75 mm (2.95 ")	583 mm (22.95 ")	976 mm (38.43 ")	758 mm (29.84 ")	405 mm (15.94 ")
54	522 mm (20.55 ")	412 mm (16.22 ")	551 mm (21.69 ")	513 mm (20.20 ")	700c	72.5°	62.4 mm (2.46 ")	43 mm (1.69 ")	118 mm (4.65 ")	75 mm (2.95 ")	602 mm (23.70 ")	995 mm (39.17 ")	773 mm (30.43 ")	405 mm (15.94 ")
56	540 mm (21.26 ")	425 mm (16.73 ")	570 mm (22.44 ")	530 mm (20.87 ")	700c	72.5°	62.4 mm (2.46 ")	43 mm (1.69 ")	137 mm (5.39 ")	75 mm (2.95 ")	622 mm (24.49 ")	1015 mm (39.96 ")	790 mm (31.10 ")	405 mm (15.94 ")
58	559 mm (22.01 ")	437 mm (17.20 ")	587 mm (23.11 ")	546 mm (21.50 ")	700c	72.5°	62.4 mm (2.46 ")	43 mm (1.69 ")	157 mm (6.18 ")	75 mm (2.95 ")	640 mm (25.20 ")	1033 mm (40.67 ")	808 mm (31.81 ")	405 mm (15.94 ")
61	587 mm (23.11 ")	443 mm (17.44 ")	600 mm (23.62 ")	567 mm (22.32 ")	700c	72.5°	62.4 mm (2.46 ")	43 mm (1.69 ")	187 mm (7.36 ")	75 mm (2.95 ")	654 mm (25.75 ")	1047 mm (41.22 ")	836 mm (32.91 ")	405 mm (15.94 ")