

Size	47	51	54	56	58	61
Rider Height CM	<166	166-174	172-180	178-186	184-192	>190
Top Tube MM (tt)	522	532	546	556	568	583
Wheelbase MM (wb)	982	999	997	1008	1020	1035
Seat Angle (sa)	74.2	74.2	74.2	74.2	74.2	74.2
Seatpost Length MM	330	380	380	380	380	430
Stack MM	516	541	562	586	610	644
Trail MM (trail)	63	63	63	63	63	63
Rear Center MM (rc)	410	410	410	410	410	410
Reach MM (reach)	374	382	386	390	394	398
Head Tube MM (ht)	112	139	156	181	206	242
Head Angle (ha)	71.2	71.2	72	72	72	72
BB Drop MM (drop)	71	71	71	71	71	71
Stem Length MM	90	90	100	110	110	120
Seat Tube MM (st)	420	457	500	522	539	573
Stem Angle	±8	±8	±8	±8	±8	±8
Post Offset MM	15	15	15	15	15	15
Crank Length MM	170	170	172.5	172.5	175	175
Fork Rake MM (fr)	50	50	45	45	45	45
Front Center MM (fc)	583	599	597	609	621	635
Fork Length MM (fl)	375	375	375	375	375	375
Bar Width MM	400	420	420	420	420	440
Bar Reach MM	70	70	70	70	70	70
Bar Drop MM	125	125	125	125	125	125