



Show Inches

Size	52cm	54cm	56cm	58cm	60cm
Recommended Rider Height	154cm–168cm	168cm–175cm	173cm–185cm	183cm–193cm	190cm–UP
A. Toptube Effective	520.0mm	540.0mm	560.0mm	580.0mm	600.0mm
B. Seat Tube Length	355.6mm	419.1mm	508.0mm	558.8mm	584.2mm
C. Headtube Angle	69°	69°	69°	69°	69°
D. Seat Tube Angle	74.5°	74.25°	74.25°	74°	73.75°
E. BB Drop	70.0mm	70.0mm	70.0mm	70.0mm	70.0mm
F. Chainstay Length	445.0mm	445.0mm	445.0mm	445.0mm	445.0mm
G. Headtube Length	90.0mm	98.0mm	127.0mm	154.0mm	175.0mm
H. Fork Length	483.0mm	483.0mm	483.0mm	483.0mm	483.0mm
J. Fork Offset	51.0mm	51.0mm	51.0mm	51.0mm	51.0mm
K. Wheelbase	1049.54mm	1067.55mm	1090.31mm	1109.83mm	1128.6mm
M. Stack	584.98mm	592.45mm	619.53mm	644.73mm	664.34mm
N. Reach	357.77mm	372.91mm	385.28mm	395.13mm	406.36mm
P. Standover	700.44mm	741.72mm	810.51mm	851.75mm	874.22mm

Show Metric

Size	52cm	54cm	56cm	58cm	60cm
Recommended Rider Height	5'1"–5'6"	5'6"–5'9"	5'8"–6'1"	6'0"–6'4"	6'3"–UP
A. Toptube Effective	20.5"	21.3"	22.0"	22.8"	23.6"
B. Seat Tube Length	14.0"	16.5"	20.0"	22.0"	23.0"
C. Headtube Angle	69°	69°	69°	69°	69°
D. Seat Tube Angle	74.5°	74.25°	74.25°	74°	73.75°

E. BB Drop	2.76"	2.76"	2.76"	2.76"	2.76"
F. Chainstay Length	17.52"	17.52"	17.52"	17.52"	17.52"
G. Headtube Length	3.54"	3.86"	5.0"	6.1"	6.9"
H. Fork Length	19.02"	19.02"	19.0"	19.0"	19.0"
J. Fork Offset	2.01"	2.01"	2.01"	2.01"	2.01"
K. Wheelbase	41.32"	42.03"	42.9"	43.7"	44.4"
M. Stack	23.03"	23.32"	24.4"	25.4"	26.2"
N. Reach	14.09"	14.68"	15.2"	15.6"	16.0"
P. Standover	27.58"	29.20"	31.9"	33.5"	34.4"

Measurements based on:

- an 483mm AC x 51mm offset fork which is equivalent to an average 100mm 29" suspension fork at 25% sag
- a 29" x 2.2" tire measuring 740mm in diameter
- Standover for all sizes is measured vertically to top of toptube from a position 50mm forward of BB center