



Geometry Size in MM:

		XS / 700	S / 700	M / 900	L / 900
A	Head Tube Angle	68.0 °	68.0 °	68.5 °	68.5 °
B	Head Tube Length	95.0 mm	100.0 mm	110.0 mm	120.0 mm
C	Top Tube Horizontal	560.0 mm	585.0 mm	600.0 mm	615.0 mm
D	Standover Height	678.0 mm	704.0 mm	750.0 mm	777.0 mm
E	BB Offset	-44.0 mm	-44.0 mm	-60.0 mm	-60.0 mm
F	BB Height	308.5 mm	308.5 mm	316.0 mm	316.0 mm
G	Wheel Base	1,087.0 mm	1,115.0 mm	1,102.0 mm	1,123.0 mm
H	BB Center to Top tube Center	311.0 mm	341.0 mm	391.0 mm	431.0 mm
I	BB Center to Top of Seat tube	355.0 mm	395.0 mm	440.0 mm	480.0 mm
K	Chainstay	435.0 mm	435.0 mm	450.0 mm	450.0 mm
L	Reach	402.0 mm	420.0 mm	419.0 mm	431.0 mm
M	Stack	552.0 mm	575.0 mm	612.0 mm	622.0 mm
N	Stem Length	50.0 mm	50.0 mm	60.0 mm	60.0 mm

Geometry Size in INCHES

		XS / 700	S / 700	M / 900	L / 900
A	Head Tube Angle	68.0 °	68.0 °	68.5 °	68.5 °
B	Head Tube Length	3.7 in	3.9 in	4.3 in	4.7 in
C	Top Tube Horizontal	22.0 in	23.0 in	23.6 in	24.2 in
D	Standover Height	26.7 in	27.7 in	29.5 in	30.6 in

E	BB Offset	-1.7 in	-1.7 in	-2.4 in	-2.4 in
F	BB Height	12.1 in	12.1 in	12.4 in	12.4 in
G	Wheel Base	42.8 in	43.9 in	43.4 in	44.2 in
H	BB Center to Toptube Center	12.2 in	13.4 in	15.4 in	17.0 in
I	BB Center to Top of Seattube	14.0 in	15.6 in	17.3 in	18.9 in
K	Chainstay	17.1 in	17.1 in	17.7 in	17.7 in
L	Reach	15.8 in	16.5 in	16.5 in	17.0 in
M	Stack	21.7 in	22.6 in	24.1 in	24.5 in
N	Stem Length	2.0 in	2.0 in	2.4 in	2.4 in