



CONTESSA SPARK

Geometry Size in MM:

		S	M	L
A	Head Tube Angle	67.2 °	67.2 °	67.2 °
B	Head Tube Length	95.0 mm	95.0 mm	105.0 mm
C	Top Tube Horizontal	575.0 mm	605.0 mm	635.0 mm
D	Standover Height	738.0 mm	746.0 mm	760.0 mm
E	BB Offset	-43.0 mm	-43.0 mm	-43.0 mm
F	BB Height	327.0 mm	327.0 mm	327.0 mm
G	Wheel Base	1,121.6 mm	1,151.6 mm	1,182.8 mm
H	BB Center to Toptube Center	345.0 mm	375.0 mm	425.0 mm
I	BB Center to Top of Seattube	410.0 mm	440.0 mm	490.0 mm
K	Chainstay	438.0 mm	438.0 mm	438.0 mm
L	Reach	402.7 mm	432.7 mm	460.0 mm
M	Stack	593.1 mm	593.1 mm	602.4 mm
N	Stem Length	50.0 mm	60.0 mm	70.0 mm
0	trail	100.2 mm	100.2 mm	100.2 mm

Geometry Size in INCHES

		S	M	L
A	Head Tube Angle	67.2 °	67.2 °	67.2 °
B	Head Tube Length	3.7 in	3.7 in	4.1 in
C	Top Tube Horizontal	22.6 in	23.8 in	25.0 in

D	Standover Height	29.1 in	29.4 in	29.9 in
E	BB Offset	-1.7 in	-1.7 in	-1.7 in
F	BB Height	12.9 in	12.9 in	12.9 in
G	Wheel Base	44.2 in	45.3 in	46.6 in
H	BB Center to Toptube Center	13.6 in	14.8 in	16.7 in
I	BB Center to Top of Seattube	16.1 in	17.3 in	19.3 in
K	Chainstay	17.2 in	17.2 in	17.2 in
L	Reach	15.9 in	17.0 in	18.1 in
M	Stack	23.4 in	23.4 in	23.7 in
N	Stem Length	2.0 in	2.4 in	2.8 in
0	trail	3.9 in	3.9 in	3.9 in