



CONTESSA SPARK

**Geometry Size in MM:**

		S	M	L
A	Head Tube Angle	68.5 °	68.5 °	68.5 °
B	Head Tube Length	95.0 mm	95.0 mm	105.0 mm
C	Top Tube Horizontal	570.0 mm	600.0 mm	630.0 mm
D	Standover Height	739.0 mm	737.0 mm	756.0 mm
E	BB Offset	-50.5 mm	-50.5 mm	-50.5 mm
F	BB Height	319.5 mm	319.5 mm	319.5 mm
G	Wheel Base	1,097.7 mm	1,127.7 mm	1,158.6 mm
H	BB Center to Top tube Center			
I	BB Center to Top of Seat tube	410.0 mm	440.0 mm	490.0 mm
K	Chainstay	435.0 mm	435.0 mm	435.0 mm
L	Reach	399.5 mm	429.5 mm	456.8 mm
M	Stack	586.9 mm	586.9 mm	596.2 mm
N	Stem Length	60.0 mm	70.0 mm	80.0 mm
0	trail	90.9 mm	90.9 mm	90.9 mm

**Geometry Size in INCHES**

		S	M	L
A	Head Tube Angle	68.5 °	68.5 °	68.5 °
B	Head Tube Length	3.7 in	3.7 in	4.1 in
C	Top Tube Horizontal	22.4 in	23.6 in	24.8 in

D	Standover Height	29.1 in	29.0 in	29.8 in
E	BB Offset	-2.0 in	-2.0 in	-2.0 in
F	BB Height	12.6 in	12.6 in	12.6 in
G	Wheel Base	43.2 in	44.4 in	45.6 in
H	BB Center to Toptube Center			
I	BB Center to Top of Seattube	16.1 in	17.3 in	19.3 in
K	Chainstay	17.1 in	17.1 in	17.1 in
L	Reach	15.7 in	16.9 in	18.0 in
M	Stack	23.1 in	23.1 in	23.5 in
N	Stem Length	2.4 in	2.8 in	3.1 in
0	trail	3.6 in	3.6 in	3.6 in