

**GENIUS eRIDE** 

## **Geometry Size in MM:**

		S / 900	S / 700	M / 900	M / 700	L/900	L / 700	XL / 900	XL / 700
		LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting
A	Head Tube Angle	64.8 °	65.4 °	64.8 °	65.4 °	65.0 °	65.6 °	65.0 °	65.6 °
В	Head Tube Length	120.0 mm	120.0 mm	125.0 mm	125.0 mm	135.0 mm	135.0 mm	145.0 mm	145.0 mm
С	Top Tube Horizontal	585.0 mm	583.4 mm	605.0 mm	603.4 mm	635.0 mm	633.3 mm	665.0 mm	663.3 mm
D	Standover Height	762.4 mm	748.8 mm	766.6 mm	753.3 mm	798.1 mm	785.4 mm	809.8 mm	797.4 mm
Е	BB Offset	-30.0 mm	-22.1 mm	-30.0 mm	-22.1 mm	-30.0 mm	-22.0 mm	-30.0 mm	-21.9 mm
F	BB Height	347.0 mm	337.9 mm	347.0 mm	337.9 mm	347.0 mm	338.0 mm	347.0 mm	338.1 mm
G	Wheel Base	1,215.2 mm	1,213.7 mm	1,236.1 mm	1,234.6 mm	1,258.4 mm	1,256.9 mm	1,290.2 mm	1,288.7 mm
Н	BB Center to Toptube Center								
I	BB Center to Top of Seattube	410.0 mm	410.0 mm	440.0 mm	440.0 mm	490.0 mm	490.0 mm	540.0 mm	540.0 mm
J	Seat Angle	75.4 °	76.0 °	75.4 °	76.0 °	74.8 °	75.4 °	74.8 °	75.4 °
K	Chainstay	465.0 mm	462.8 mm						
L	Reach	421.8 mm	428.3 mm	440.6 mm	447.1 mm	460.7 mm	467.2 mm	488.3 mm	494.7 mm

M	Stack	626.6 mm	622.2 mm	631.2 mm	626.6 mm	641.4 mm	636.7 mm	650.4 mm	645.6 mm
N	Stem Length	50.0 mm	50.0 mm	50.0 mm	50.0 mm	60.0 mm	60.0 mm	70.0 mm	70.0 mm
0	Trail	128.8 mm	120.2 mm	128.8 mm	120.2 mm	127.2 mm	118.8 mm	127.2 mm	118.8 mm

## **Geometry Size in INCHES**

		S / 900	S / 700	M / 900	M / 700	L / 900	L / 700	XL / 900	XL / 700
		LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting
A	Head Tube Angle	64.8 °	65.4 °	64.8 °	65.4 °	65.0 °	65.6 °	65.0 °	65.6 °
В	Head Tube Length	4.7 in	4.7 in	4.9 in	4.9 in	5.3 in	5.3 in	5.7 in	5.7 in
С	Top Tube Horizontal	23.0 in	23.0 in	23.8 in	23.8 in	25.0 in	24.9 in	26.2 in	26.1 in
D	Standover Height	30.0 in	29.5 in	30.2 in	29.7 in	31.4 in	30.9 in	31.9 in	31.4 in
Е	BB Offset	-1.2 in	-0.9 in						
F	BB Height	13.7 in	13.3 in						
G	Wheel Base	47.8 in	47.8 in	48.7 in	48.6 in	49.5 in	49.5 in	50.8 in	50.7 in
Н	BB Center to Toptube Center								
I	BB Center to Top of Seattube	16.1 in	16.1 in	17.3 in	17.3 in	19.3 in	19.3 in	21.3 in	21.3 in
J	Seat Angle	75.4 °	76.0 °	75.4 °	76.0 °	74.8 °	75.4 °	74.8 °	75.4 °
K	Chainstay	18.3 in	18.2 in						
L	Reach	16.6 in	16.9 in	17.3 in	17.6 in	18.1 in	18.4 in	19.2 in	19.5 in
М	Stack	24.7 in	24.5 in	24.8 in	24.7 in	25.3 in	25.1 in	25.6 in	25.4 in
N	Stem Length	2.0 in	2.0 in	2.0 in	2.0 in	2.4 in	2.4 in	2.8 in	2.8 in
0	Trail	5.1 in	4.7 in	5.1 in	4.7 in	5.0 in	4.7 in	5.0 in	4.7 in