



**Geometry Size in INCHES:**

		S / 900	S / 700	M / 900	M / 700	L / 900	L / 700	XL / 900	XL / 700
		LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting
A	Head Tube Angle	65.0 °	65.6 °	65.4 °	66.0 °	65.4 °	66.0 °	65.4 °	66.0 °
B	Head Tube Length	4.9 in	4.9 in	4.9 in	4.9 in	5.3 in	5.3 in	5.7 in	5.7 in
C	Top Tube Horizontal	22.9 in	22.8 in	23.9 in	23.8 in	24.9 in	24.8 in	25.7 in	25.6 in
D	Standover Height	30.3 in	29.6 in	30.3 in	29.7 in	31.5 in	30.9 in	32.6 in	32.0 in
E	BB Offset	-1.0 in	-0.7 in	-1.0 in	-0.7 in	-1.0 in	-0.7 in	-1.0 in	-0.7 in
F	BB Height	13.8 in	13.5 in	13.8 in	13.5 in	13.8 in	13.5 in	13.8 in	13.5 in
G	Wheel Base	47.1 in	47.0 in	47.9 in	47.8 in	48.9 in	48.8 in	49.7 in	49.7 in
H	BB Center to Toptube Center								
I	BB Center to Top of Seattube	16.1 in	16.1 in	17.3 in	17.3 in	19.3 in	19.3 in	21.3 in	21.3 in
J	Seat Angle	73.8 °	74.5 °	73.9 °	74.5 °	73.9 °	74.5 °	73.9 °	74.5 °
K	Chainstay	18.2 in	18.1 in	18.2 in	18.1 in	18.2 in	18.1 in	18.2 in	18.1 in
L	Reach	16.0 in	16.3 in	17.0 in	17.2 in	17.8 in	18.1 in	18.5 in	18.8 in
M	Stack	23.9 in	23.7 in	24.0 in	23.8 in	24.4 in	24.2 in	24.7 in	24.5 in
N	Stem Length		2.0 in	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in
O	Trail	4.8 in	4.3 in	4.6 in	4.2 in	4.6 in	4.2 in	4.6 in	4.2 in

**Geometry Size in MM:**

		S / 900	S / 700	M / 900	M / 700	L / 900	L / 700	XL / 900	XL / 700
		LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting
A	Head Tube Angle	65.0 °	65.6 °	65.4 °	66.0 °	65.4 °	66.0 °	65.4 °	66.0 °
B	Head Tube Length	125.0 mm	125.0 mm	125.0 mm	125.0 mm	135.0 mm	135.0 mm	145.0 mm	145.0 mm
C	Top Tube Horizontal	581.8 mm	580.0 mm	606.8 mm	605.0 mm	631.9 mm	630.0 mm	651.9 mm	650.0 mm
D	Standover Height	768.5 mm	752.8 mm	769.2 mm	753.8 mm	800.9 mm	786.0 mm	827.4 mm	812.8 mm
E	BB Offset	-26.0 mm	-18.0 mm	-26.1 mm	-18.0 mm	-26.2 mm	-18.0 mm	-26.3 mm	-18.0 mm
F	BB Height	351.0 mm	342.0 mm	350.9 mm	342.0 mm	350.8 mm	342.0 mm	350.8 mm	342.0 mm
G	Wheel Base	1,195.3 mm	1,193.7 mm	1,215.6 mm	1,214.0 mm	1,242.1 mm	1,240.6 mm	1,263.6 mm	1,262.0 mm
H	BB Center to Top tube Center								
I	BB Center to Top of Seattube	410.0 mm	410.0 mm	440.0 mm	440.0 mm	490.0 mm	490.0 mm	540.0 mm	540.0 mm
J	Seat Angle	73.8 °	74.5 °	73.9 °	74.5 °	73.9 °	74.5 °	73.9 °	74.5 °
K	Chainstay	462.2 mm	460.0 mm	462.2 mm	460.0 mm	462.2 mm	460.0 mm	462.2 mm	460.0 mm
L	Reach	406.3 mm	412.9 mm	430.8 mm	437.2 mm	453.3 mm	459.7 mm	470.8 mm	477.2 mm
M	Stack	607.1 mm	602.6 mm	609.5 mm	604.8 mm	618.8 mm	614.0 mm	628.0 mm	623.1 mm
N	Stem Length		50.0 mm	50.0 mm	50.0 mm	50.0 mm	50.0 mm	50.0 mm	50.0 mm
O	Trail	120.9 mm	109.6 mm	117.8 mm	106.7 mm	117.7 mm	106.7 mm	117.6 mm	106.7 mm