



### Geometry Chart (MM)

	48	51	54	56	58	61
STACK	485MM	506MM	522MM	540MM	559MM	587MM
REACH	381MM	398MM	412MM	425MM	437MM	443MM
EFFECTIVE TOP TUBE @75&DEG SEAT TUBE	511MM	533MM	551MM	570MM	587MM	600MM
EFFECTIVE TOP TUBE @79&DEG SEAT TUBE	475MM	496MM	513MM	530MM	546MM	567MM
WHEEL SIZE	700C	700C	700C	700C	700C	700C
HEAD TUBE ANGLE	71°	72.5°	72.5°	72.5°	72.5°	72.5°
TRAIL *	62.4MM	62.4MM	62.4MM	62.4MM	62.4MM	62.4MM
FORK OFFSET	52MM	43MM	43MM	43MM	43MM	43MM
HEAD TUBE LENGTH	87.5MM	101MM	118MM	137MM	157MM	187MM
BOTTOM BRACKET DROP	75MM	75MM	75MM	75MM	75MM	75MM
FRONT CENTER	582MM	583MM	602MM	622MM	640MM	654MM
WHEELBASE	975MM	976MM	995MM	1015MM	1033MM	1047MM
STANDOVER HEIGHT	732MM	758MM	773MM	790MM	808MM	836MM
CHAINSTAY LENGTH	405MM	405MM	405MM	405MM	405MM	405MM

### Geometry Chart (INCHES)

	48	51	54	56	58	61
STACK	19.09"	19.92"	20.55"	21.26"	22.01"	23.11"
REACH	15.00"	15.67"	16.22"	16.73"	17.20"	17.44"

EFFECTIVE TOP TUBE @75&DEG SEAT TUBE	20.12"	20.98"	21.69"	22.44"	23.11"	23.62"
EFFECTIVE TOP TUBE @79&DEG SEAT TUBE	18.70"	19.53"	20.20"	20.87"	21.50"	22.32"
WHEEL SIZE	700C	700C	700C	700C	700C	700C
HEAD TUBE ANGLE	71°	72.5°	72.5°	72.5°	72.5°	72.5°
TRAIL *	2.46"	2.46"	2.46"	2.46"	2.46"	2.46"
FORK OFFSET	2.05"	1.69"	1.69"	1.69"	1.69"	1.69"
HEAD TUBE LENGTH	3.44"	3.98"	4.65"	5.39"	6.18"	7.36"
BOTTOM BRACKET DROP	2.95"	2.95"	2.95"	2.95"	2.95"	2.95"
FRONT CENTER	22.91"	22.95"	23.70"	24.49"	25.20"	25.75"
WHEELBASE	38.39"	38.43"	39.17"	39.96"	40.67"	41.22"
STANDOVER HEIGHT	28.82"	29.84"	30.43"	31.10"	31.81"	32.91"
CHAINSTAY LENGTH	15.94"	15.94"	15.94"	15.94"	15.94"	15.94"