



| AR(3.0) | XS 48cm | S 51cm | M 54cm | L 56cm | XL 58cm | XXL 61cm |
|--------------------------------------|----------------------|---------------------|---------------------|---------------------|----------------------|-----------------------|
| (A) HEAD TUBE ANGLE | 71 | 72.1 | 73 | 73.5 | 74 | 74 |
| (B) SEAT TUBE ANGLE | 74.3 | 74.4 | 73.5 | 73.5 | 73.5 | 73 |
| (C) TOP TUBE LENGTH (EFFECTIVE) | 509 | 529 | 543 | 560 | 580 | 605 |
| (D) HEAD TUBE LENGTH | 97 | 111 | 130 | 150 | 167 | 197.5 |
| (E) SEAT TUBE LENGTH (CENTER TO TOP) | 441 | 473 | 502.5 | 526 | 553 | 601 |
| (F) STAND OVER HEIGHT | 705 | 734 | 760 | 780 | 807 | 845 |
| (G) BOTTOM BRACKET DROP | 72 | 70 | 70 | 70 | 70 | 70 |
| (H) REAR CENTER | 408 | 408 | 410 | 410 | 410 | 412 |
| (I) FRONT CENTER | 577 | 579 | 580 | 588 | 603 | 622 |
| (J) WHEELBASE | 974 | 977 | 980 | 988 | 1003 | 1024 |
| (K) FORK LENGTH | 373.5 | 373.5 | 373.5 | 373.5 | 373.5 | 373.5 |
| (L) FORK OFFSET | 52 | 47 | 47 | 43 | 43 | 43 |
| (M) STACK | 501 | 518 | 539 | 561 | 579 | 608 |
| (N) REACH | 370 | 381 | 383 | 394 | 408 | 419 |