



|                     | <b>S</b> | <b>M</b> | <b>L</b> | <b>XL</b> |
|---------------------|----------|----------|----------|-----------|
| A Stack             | 628.2    | 646.9    | 665.5    | 679.4     |
| B Reach             | 340      | 355      | 370      | 381.6     |
| C Headtube Angle    | 68.5     | 68.5     | 68.5     | 68.5      |
| D Headtube Length   | 210      | 230      | 250      | 265       |
| E Seattube Angle    | 67       | 67       | 67       | 67        |
| F Seattube Length   | 382      | 406      | 444      | 470       |
| G Toptube Effective | 606.7    | 629.6    | 652.5    | 670       |
| H BB Height         | 276.5    | 276.5    | 276.5    | 276.5     |
| I BB Drop           | 68       | 68       | 68       | 68        |
| J Chainstay         | 490      | 490      | 490      | 490       |
| K Wheelbase         | 1089     | 1111     | 1134     | 1151      |
| L Standover Height  | 618.44   | 618.48   | 674.72   | 675.89    |
| M Fork Offset       | 40       | 40       | 40       | 40        |
| Seatpost Diameter   | 30.9     | 30.9     | 30.9     | 30.9      |
| Handlebar Width     | 700      | 700      | 700      | 700       |
| Stem Length         | 45       | 45       | 45       | 45        |
| Crank Length        | 170      | 170      | 170      | 170       |