

# Bottom Bracket Compatibility Matrix

Road

Commonly used by	Frame standard	Inner dia. mm	Shell width mm	Crank types					
				All Shimano compatible (24 mm)	SRAM GXP (24/22.2 mm)	Campagnolo Ultra Torque (25 mm)	Campagnolo Pro-Tech (25mm)	SRAM DUB Road (29 mm)	30 mm*
Specialized	BSA Thread	-	68						
Pinarello	ITA Thread	-	70						
Colnago	T45	-	82.5						
Ventum, Quintana Roo	T47-68	-	68						
Factor	T47A	-	77						
Trek	T47-86	-	86						
Giant, BMC, Scott, Canyon	BB86	41	86.5						
Ventum	PF30	46	68						
Cervélo	BBright	46	79						
Open, 3T, Orbea	EVO386	46	86.5						
Specialized, Cannondale	BB30	42	68						

\* 30 mm cranks with a short spindle may have limited compatibility.  
 ▲ Gravel compatible Bottom Brackets

MTB

Commonly used by	Frame standard	Inner dia. mm	Shell width mm	Crank types			
				All Shimano compatible (24 mm)	SRAM GXP (24/22.2 mm)	SRAM DUB (29 mm)	BB30 (30mm)
Specialized	BSA Thread	-	73				
Trek, Giant, BMC, Scott, Canyon	BB92 (BB86/89)	41	89.5/91.5				
Cannondale	BB30	42	83				
Cannondale, Niner	PF30	46	73				
	T47 - 73	-	73				

- All road bottom brackets are standard with a 4-year warranty. Choose a coated version for even lower friction and lifetime warranty
- Gravel bottom brackets use Road compatibility and built with long life grease and are coated only with lifetime warranty
- All MTB bottom brackets are coated only with lifetime warranty
- Special BB65 LOOK bearings available
- BB90 Bearings for Shimano and GXP available
- Most products are available in both black and red
- See installation and maintenance videos on [ceramicspeed.com](https://ceramicspeed.com) → Support or scan this QR code for direct access
- For best performance and longevity, always service with one of the three CeramicSpeed UFO Grease options:



All-Round Grease



Long-Life Grease



Race Day Grease