

Geometry Chart (MM)

| | 48 | 51 | 54 | 56 | 58 | 61 |
|--------------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| Reach mm | 360 | 369 | 378 | 387 | 396 | 405 |
| Stack mm | 505 | 530 | 555 | 580 | 605 | 630 |
| Head Tube Angle | 70.5° | 71.5° | 72° | 72° | 72° | 72° |
| Front Center mm | 579.4 | 581.7 | 591.5 | 608.5 | 626 | 643 |
| Bottom Bracket Drop mm | 76.5 | 76.5 | 74 | 74 | 71.5 | 71.5 |
| Head Tube Length mm | 89.5 | 109.9 | 136 | 162.3 | 191.2 | 217.5 |
| Top Tube Length mm | 502 | 522 | 543 | 565 | 581 | 598 |
| Seat Tube Angle | 74.5° | 74° | 73.5° | 73° | 73° | 73° |
| Standover Height mm | 712 | 752 | 784 | 807 | 834 | 857 |
| Trail mm | 60 | 60 | 60 | 60 | 60 | 60 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C |
| Fork Offset mm | 59 | 53 | 50 | 50 | 50 | 50 |
| Wheelbase mm | 982.2 | 984.5 | 995.2 | 1012.3 | 1030.7 | 1047.8 |
| Chainstay Length mm | 415 | 415 | 415 | 415 | 415 | 415 |