

Geometry Chart (MM)

| | 48 | 51 | 54 | 56 | 58 | 61 |
|---|-----------|-----------|-----------|-----------|-----------|-----------|
| Reach mm | 381 | 398 | 412 | 425 | 437 | 443 |
| Stack mm | 485 | 506 | 522 | 540 | 559 | 587 |
| Head Tube Angle | 71° | 72.5° | 72.5° | 72.5° | 72.5° | 72.5° |
| Front Center mm | 582 | 583 | 602 | 622 | 640 | 654 |
| Bottom Bracket Drop mm | 75 | 75 | 75 | 75 | 75 | 75 |
| Head Tube Length mm | 87.5 | 101 | 118 | 137 | 157 | 187 |
| Standover Height mm | 732 | 758 | 773 | 790 | 808 | 836 |
| Trail mm | 62.4 | 62.4 | 62.4 | 62.4 | 62.4 | 62.4 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C |
| Fork Offset mm | 52 | 43 | 43 | 43 | 43 | 43 |
| Wheelbase mm | 975 | 976 | 995 | 1015 | 1033 | 1047 |
| Chainstay Length mm | 405 | 405 | 405 | 405 | 405 | 405 |
| Effective Top Tube @75&Deg Seat Tube mm | 511 | 533 | 551 | 570 | 587 | 600 |
| Effective Top Tube @79&Deg Seat Tube mm | 475 | 496 | 513 | 530 | 546 | 567 |