

**Geometry Chart (MM)**

|                          | <b>48</b> | <b>51</b> | <b>54</b> | <b>56</b> | <b>58</b> |
|--------------------------|-----------|-----------|-----------|-----------|-----------|
| Reach   mm               | 367       | 376       | 384       | 392       | 401       |
| Stack   mm               | 496       | 519       | 542       | 565       | 588       |
| Head Tube Angle          | 71°       | 72°       | 73°       | 73.5°     | 73.5°     |
| Front Center   mm        | 579       | 580       | 581       | 588       | 604       |
| Bottom Bracket Drop   mm | 72.5      | 72.5      | 70        | 70        | 67.5      |
| Head Tube Length   mm    | 69        | 87        | 109       | 130       | 157       |
| Top Tube Length   mm     | 520       | 535       | 550       | 565       | 581       |
| Seat Tube Angle          | 73°       | 73°       | 73°       | 73°       | 73°       |
| Standover Height   mm    | 715       | 736       | 754       | 782       | 813       |
| Trail   mm               | 56.1      | 56.1      | 56.2      | 56.2      | 56.2      |
| Wheel Size               | 700C      | 700C      | 700C      | 700C      | 700C      |
| Fork Offset   mm         | 58        | 52        | 46        | 43        | 43        |
| Wheelbase   mm           | 973       | 974       | 975       | 982       | 999       |
| Chainstay Length   mm    | 405       | 405       | 405       | 405       | 405       |