


AR



Geometry Chart

	48	51	54	56	58	61
(A) Top Tube Length	509 mm	529 mm	543 mm	560 mm	580 mm	605 mm
(B) Seat Tube Length	441 mm	473 mm	502.5 mm	526 mm	553 mm	601 mm
(C) Seat Tube Angle	74.3 °	74.4 °	73.5 °	73.5 °	73.5 °	73 °
(D) Head Tube Length	97 mm	111 mm	130 mm	150 mm	167 mm	197.5 mm
(E) Steering Angle	71 °	72.1 °	73 °	73.5 °	73.5 °	73 °
(F) Chain Stay Length	408 mm	408 mm	410 mm	410 mm	410 mm	412 mm
(G) Wheel Base	974 mm	977 mm	980 mm	988 mm	1003 mm	1024 mm
(H) Standover Height	705 mm	734 mm	760 mm	780 mm	807 mm	845 mm
(I) BB-Drop	72 mm	70 mm	70 mm	70 mm	70 mm	70 mm
(K) Fork Offset	52 mm	47 mm	47 mm	43 mm	43 mm	43 mm
(L) Stack	501 mm	518 mm	539 mm	561 mm	579 mm	608 mm
(M) Reach	370 mm	381 mm	383 mm	394 mm	408 mm	419 mm
(N) Stem Length	90 mm	90 mm	100 mm	100 mm	110 mm	120 mm
(O) Crank Length	165 mm	170 mm	172.5 mm	172.5 mm	175 mm	175 mm