



Geometry Chart

| | 45 | 48 | 51 | 54 | 58 | 61 | 56 |
|-----------------------|----------|----------|----------|----------|-----------|-----------|----------|
| (A) Top Tube Length | 494.8 mm | 512 mm | 526.2 mm | 546.6 mm | 581.4 mm | 600.3 mm | 558.1 mm |
| (B) Seat Tube Length | 405 mm | 426 mm | 467 mm | 507 mm | 558 mm | 594.6 mm | 527 mm |
| (C) Seat Tube Angle | 75.3 ° | 74.5 ° | 74 ° | 73.5 ° | 73.3 ° | 73 ° | 73.5 ° |
| (D) Head Tube Length | 90 mm | 100 mm | 115 mm | 135 mm | 177 mm | 205 mm | 155 mm |
| (E) Steering Angle | 70.5 ° | 71.5 ° | 72.4 ° | 72.6 ° | 73.8 ° | 73.8 ° | 73.2 ° |
| (F) Chain Stay Length | 406 mm | 406 mm | 406 mm | 408 mm | 410 mm | 410 mm | 408 mm |
| (G) Wheel Base | 967.4 mm | 969.4 mm | 971.4 mm | 982.1 mm | 1005.3 mm | 1020.4 mm | 988.2 mm |
| (H) Standover Height | 704 mm | 720.6 mm | 750 mm | 782 mm | 827.9 mm | 860.8 mm | 802 mm |
| (I) BB-Drop | 74 mm | 74 mm | 74 mm | 72 mm | 72 mm | 72 mm | 72 mm |
| (J) BB Height | 266.3 mm | 266.3 mm | 266.3 mm | 268.3 mm | 268.3 mm | 268.3 mm | 268.3 mm |
| (K) Fork Offset | 51 mm | 51 mm | 51 mm | 45 mm | 45 mm | 45 mm | 45 mm |
| (L) Stack | 496.2 mm | 509.2 mm | 526.6 mm | 546.2 mm | 590.5 mm | 617.4 mm | 567.3 mm |
| (M) Reach | 364.6 mm | 370.8 mm | 375.2 mm | 384.8 mm | 404.2 mm | 411.5 mm | 390 mm |
| (N) Stem Length | 80 mm | 80 mm | 90 mm | 100 mm | 110 mm | 120 mm | 100 mm |
| (O) Crank Length | 167.5 mm | 167.5 mm | 170 mm | 172.5 mm | 175 mm | 175 mm | 172.5 mm |