



### Geometry Chart

	47	51	54	56	58	61
(A) Top Tube Length	510 mm	525 mm	545 mm	563 mm	580 mm	595 mm
(B) Seat Tube Length	430 mm	450 mm	480 mm	500 mm	520 mm	550 mm
(C) Seat Tube Angle	74.7 °	74.5 °	74 °	73.5 °	73 °	73 °
(D) Head Tube Length	130 mm	145 mm	165 mm	185 mm	205 mm	225 mm
(E) Steering Angle	71.3 °	72 °	72.5 °	72.5 °	72.5 °	72.5 °
(F) Chain Stay Length	415 mm	417 mm	417 mm	417 mm	417 mm	417 mm
(G) Wheel Base	981 mm	989 mm	1000 mm	1013 mm	1027 mm	1042 mm
(H) Standover Height	687 mm	708 mm	737 mm	757 mm	777 mm	805 mm
(I) BB-Drop	72 mm	70 mm	70 mm	70 mm	70 mm	70 mm
(K) Fork Offset	52 mm	50 mm	50 mm	50 mm	50 mm	50 mm
(L) Stack	539 mm	555 mm	576 mm	595 mm	614 mm	633 mm
(M) Reach	362 mm	369 mm	379 mm	386 mm	392 mm	401 mm
(N) Stem Length	80 mm	90 mm	100 mm	100 mm	110 mm	120 mm
(O) Crank Length	165 mm	170 mm	172.5 mm	172.5 mm	175 mm	175 mm