

FRAME	All New Unidirectional Carbon Fiber Front Triangle, Series 4 Alloy Rear End, 29" Wheels, 150mm Travel MultiTrac Suspension Platform, Internal Dropper Post and Rear Derailleur Routing, Chainstay Mounted Post Mount Disc Brake, 148x12mm Boost Thru- Axle, 73mm Threaded BB w/ ISCG05 Tabs
FORK	Fox 38 Performance Elite, 160mm Travel, 29°, 110x15mm Boost Kabolt Thru-Axle, 44mm Offset, Integrated Fox Fender
ѕноск	Fox Float DPX2, Performance, EVOL Air Spring, 3 Position Compression Adjustment, Rebound Adjustment, 205x65mm, Trunnion Upper Mount, 25mmxM8 Lower Mount
RIMS	Marin, Double Wall Alloy, 29mm Inner, Welded Joint, Disc Specific, 32H, Tubeless Compatible
HUB REAR	Shimano HB-MT510B, 148x12mm, Disc, Microspline Freehub Body
HUB FRONT	Shimano HF-MT410B, 110x15mm, Disc
SPOKES	14g Black Stainless Steel
TIRES	Front: Maxxis Assegai 29x2.5", MAXX TERRA EXO+, Tubeless Compatible; Rear: Maxxis Assegai 29x2.5", MAXX GRIP, DoubleDown, Tubeless Compatible
DERAILLEUR REAR	Shimano XT 12-Speed, SGS
SHIFT LEVER	Shimano SLX 12-Speed, I-Spec EV
CRANKSET	FSA Gradient, Modular 1x, 32T Direct Mount Chainring, MegaTooth Technology, Mego EXC Spindle, Boost Spacing
BOTTOM BRACKET	MEGAEVO BB, 73mm BSA Threaded

CHAIN	KMC X-12 Silver and Black
CASSETTE	Shimano SLX M7100 Cassette, 12-Speed, 10-51T
BRAKES FRONT	Shimano SLX, 4-Piston Hydraulic Disc, 203mm Rotor
BRAKES REAR	Shimano SLX, 4-Piston Hydraulic Disc, 180mm Rotor
BRAKE LEVERS	Shimano SLX Hydraulic, I-Spec EV
HANDLEBAR	Race Face Affect R 35, 35mm Clamp, 780n Width, 20mm Rise, 5° Up, 8° Back
STEM	Race Face Affect R 35, 50mm Length
GRIPS	Marin Single Clamp Locking
HEADSET	FSA No 57, Sealed Cartridge Bearings, 1 1/x 1 1/2"
SEATPOST	X-Fusion Manic, 1x Shimano I-Spec EV Remote, Size S 125mm Travel, Size M and L 150mm Travel, Size XL 170mm Travel, 30.9mm
SADDLE	Marin Trail Speed Concept Pro
EXTRAS	Bolt-On Thru-Axle, Downtube Protector