



Geometry Chart

Size	SM- 160mmFork	MD- 160mmFork	LG- 160mmFork	XL- 160mmFork	SM- 150mmFork	MD- 150mmFork	LG- 150mmFork	XL- 150mmFork
A.EffectiveTopTube	594/593	616/615	640/639	663/662	593/592	615/614	639/638	662/661
B.StandOver	726/728	729/732	730/733	730/733	720/723	724/727	725/728	725/728
C.Reach	448/451	469/472	490/493	510/514	452/456	473/476	494/497	515/518
D.Stack	611/609	615/613	624/622	633/630	608/605	612/609	621/618	629/627
E.TotalSeatTubeLength	405	430	455	480	405	430	455	480
F.HeadtubeLength	95	100	110	120	95	100	110	120
G.HeadtubeAngle	64.6/64.9	64.6/64.9	64.6/64.9	64.6/64.9	65.0/65.3	65.0/65.3	65.0/65.3	65.0/65.3
H.SeatTubeAngle	76.5/76.8	76.5/76.8	76.5/76.8	76.5/76.8	76.9/77.2	76.9/77.2	76.9/77.2	76.9/76.2
I.BBDrop	26/22	26/22	26/21	26/21	29/25	29/25	29/25	29/25
K.ChainstayLength	432/431	432/431	432/431	432/431	17.0/17.0	432/431	432/431	432/431
L.ForkLengthAxletoCrown	569	569	569	569	559	559	559	559
M.ForkOffset	43	43	43	43	43	43	43	43
N.Wheelbase	1204/1204	1228/1227	1253/1252	1278/1278	1200/1200	1223/1223	1249/1248	1274/1274
CrankArmLength	165	170	170	175	165	170	170	175
HandlebarWidth	seebuildkit	seebuildkit	seebuildkit	seebuildkit	seebuildkit	seebuildkit	seebuildkit	seebuildkit
RecommendedRiderHeight	165cm- 173cm	173cm- 180cm	180cm- 188cm	188cm-UP	165cm- 173cm	173cm- 180cm	180cm- 188cm	188cm-UP
StemLength	50	50	50	50	50	50	50	50

Measurements based on

- an unsprung bike (no sag) a 29 x 2.4" tire measuring 746mm in diameter Standover is measured from vertically from ground to top of top tube 50mm forward of bottom bracket, subtract 9mm (0.3") for 27.5 x 2.8" tires
- Note: Where two measurements are listed, the first number is with Flip Chip in Low position; the second number is with Flip Chip in High position