



Geometry Chart

| Size | SM | MD | LG | XL |
|--------------------------------|-------------|-------------|-------------|-----------|
| A.EffectiveTopTube | 596/595 | 618/617 | 639/639 | 661/660 |
| B.StandOver | 750/753 | 748/758 | 759/769 | 769/780 |
| C.Reach | 413/415 | 432/434 | 451/453 | 470/472 |
| D.Stack | 613/611 | 622/620 | 632/629 | 641/639 |
| E.TotalSeatTubeLength | 419 | 444 | 483 | 520 |
| F.HeadtubeLength | 103 | 113 | 123 | 133 |
| G.HeadtubeAngle | 66.8/67.0 | 66.8/67.0 | 66.8/67.0 | 66.8/67.0 |
| H.SeatTubeAngle | 73.4/73.6 | 73.4/73.6 | 73.4/73.6 | 73.4/73.6 |
| I.BBDrop | 29/26 | 29/26 | 29/26 | 29/26 |
| K.ChainstayLength | 432/431 | 432/431 | 432/431 | 432/431 |
| L.ForkLengthAxletoCrown | 551 | 551 | 551 | 551 |
| M.ForkOffset | 44 | 44 | 44 | 44 |
| N.Wheelbase | 1141 | 1164 | 1187 | 1209 |
| CrankArmLength | 165 | 170 | 170 | 175 |
| HandlebarWidth | 800 | 800 | 800 | 800 |
| RecommendedRiderHeight | 165cm-173cm | 173cm-180cm | 180cm-188cm | 188cm-UP |
| StemLength | 50 | 50 | 50 | 50 |

Measurements based on

- An unsprung bike (no sag) A 29 x 2.4" tire measuring 745mm in diameter Standover is measured from vertically from ground to bend in top tube, subtract 2-8mm (0.1-0.3") for 27.5 x 2.8-3.0" tires
- Measurements shown are for LOW / HIGH Flip Chip settings