



Geometry Chart

Size	SM	MD	LG	XL
A.EffectiveTopTube	596/595	618/617	639/639	661/660
B.StandOver	750/753	748/758	759/769	769/780
C.Reach	413/415	432/434	451/453	470/472
D.Stack	613/611	622/620	632/629	641/639
E.TotalSeatTubeLength	419	444	483	520
F.HeadtubeLength	103	113	123	133
G.HeadtubeAngle	66.8/67.0	66.8/67.0	66.8/67.0	66.8/67.0
H.SeatTubeAngle	73.4/73.6	73.4/73.6	73.4/73.6	73.4/73.6
I.BBDrop	29/26	29/26	29/26	29/26
K.ChainstayLength	432/431	432/431	432/431	432/431
L.ForkLengthAxletoCrown	551	551	551	551
M.ForkOffset	44	44	44	44
N.Wheelbase	1141	1164	1187	1209
CrankArmLength	165	170	170	175
HandlebarWidth	800	800	800	800
RecommendedRiderHeight	165cm-173cm	173cm-180cm	180cm-188cm	188cm-UP
StemLength	50	50	50	50

Measurements based on

- An unsprung bike (no sag) A 29 x 2.4" tire measuring 745mm in diameter Standover is measured from vertically from ground to bend in top tube, subtract 2-8mm (0.1-0.3") for 27.5 x 2.8-3.0" tires
- Measurements shown are for LOW / HIGH Flip Chip settings