



### Geometry Chart

Size	XS	SM	MD	LG	XL	
<b>A.EffectiveTopTube</b>	550	570	600	625	650	
<b>B.StandOver</b>	606	641	677	713	749	796
<b>C.Reach</b>	393	404	423	436	450	
<b>D.Stack</b>	514	542	580	617	655	
<b>E.TotalSeatTubeLength</b>	340	380	450	490	530	
<b>F.HeadtubeLength</b>	90	120	160	200	240	
<b>G.HeadtubeAngle</b>	69.5	69.5	69.5	69.5	69.5	
<b>H.SeatTubeAngle</b>	73	73	73	73	73	
<b>I.BBDrop</b>	70	70	70	70	70	
<b>K.ChainstayLength</b>	440	440	440	440	440	
<b>L.ForkLengthAxletoCrown</b>	402	402	402	402	402	
<b>M.ForkOffset</b>	50	50	50	50	50	
<b>N.Wheelbase</b>	1047	1069	1101	1129	1156	
<b>CrankArmLength</b>	165	170	172.5	175	175	
<b>HandlebarWidth</b>	700	700	700	700	700	
<b>RecommendedRiderHeight</b>	142-155cm	152-165cm	163-175cm	173-185cm	183-196cm	
<b>StemLength</b>	60	70	70	80	90	

### Measurements based on

- a fork measuring 405mm with 50mm offset a 700 x 38mm tire measuring 706 mm in diameter
- Stand over measured vertically to top of top tube from a position 50mm forward of BB center