



### Geometry Chart

| Size                           | XS        | SM        | MD        | LG        | XL        |     |
|--------------------------------|-----------|-----------|-----------|-----------|-----------|-----|
| <b>A.EffectiveTopTube</b>      | 550       | 570       | 600       | 625       | 650       |     |
| <b>B.StandOver</b>             | 606       | 641       | 677       | 713       | 749       | 796 |
| <b>C.Reach</b>                 | 393       | 404       | 423       | 436       | 450       |     |
| <b>D.Stack</b>                 | 514       | 542       | 580       | 617       | 655       |     |
| <b>E.TotalSeatTubeLength</b>   | 340       | 380       | 450       | 490       | 530       |     |
| <b>F.HeadtubeLength</b>        | 90        | 120       | 160       | 200       | 240       |     |
| <b>G.HeadtubeAngle</b>         | 69.5      | 69.5      | 69.5      | 69.5      | 69.5      |     |
| <b>H.SeatTubeAngle</b>         | 73        | 73        | 73        | 73        | 73        |     |
| <b>I.BBDrop</b>                | 70        | 70        | 70        | 70        | 70        |     |
| <b>K.ChainstayLength</b>       | 440       | 440       | 440       | 440       | 440       |     |
| <b>L.ForkLengthAxletoCrown</b> | 402       | 402       | 402       | 402       | 402       |     |
| <b>M.ForkOffset</b>            | 50        | 50        | 50        | 50        | 50        |     |
| <b>N.Wheelbase</b>             | 1047      | 1069      | 1101      | 1129      | 1156      |     |
| <b>CrankArmLength</b>          | 165       | 170       | 170       | 172.5     | 175       |     |
| <b>HandlebarWidth</b>          | 700       | 700       | 700       | 700       | 700       |     |
| <b>RecommendedRiderHeight</b>  | 142-155cm | 152-165cm | 163-175cm | 173-185cm | 183-196cm |     |
| <b>StemLength</b>              | 60        | 70        | 70        | 80        | 90        |     |

### Measurements based on

- a fork measuring 405mm with 50mm offset a 700 x 38mm tire measuring 706 mm in diameter
- Stand over measured vertically to top of top tube from a position 50mm forward of BB center