



Geometry Chart

Size	XS	SM	MD	LG	XL
A.EffectiveTopTube	568.2	590.5	614.8	643.5	670.1
B.StandOver	678.6	698.3	737.2	769.1	798.7
C.Reach	395	416	439	465	489
D.Stack	605.6	610.2	614.9	624.2	633.4
E.TotalSeatTubeLength	355	381	431	470	508
F.HeadtubeLength	95	100	105	115	125
G.HeadtubeAngle	68	68	68	68	68
H.SeatTubeAngle	74	74	74	74	74
I.BBDrop	58	58	58	58	58
K.ChainstayLength	439	439	439	439	439
L.ForkLengthAxletoCrown	510	510	510	510	510
M.ForkOffset	46	46	46	46	46
N.Wheelbase	1100.6	1123.4	1148.3	1178	1205.8
CrankArmLength	170	170	175	175	175
HandlebarWidth	750mm	750mm	800mm	800mm	800mm
RecommendedRiderHeight	157cm-168cm	160cm-175cm	173cm-183cm	180cm-191cm	188cm-UP
StemLength	60	60	60	60	60

Measurements based on

- OE spec 120mm 29/27.5+ suspension fork at 25% sag 27.5 x 2.8" tire measuring 722mm in diameter
- Standover is measured from vertically from ground to the top of the toptube, 50mm forward of the BB. Add 8-12.5mm (0.3-0.5") for 29 x 2.4-2.6" wheels/tires