



Geometry Chart

| Size | XS | SM | MD | LG | XL |
|--------------------------------|-------------|-------------|-------------|-------------|----------|
| A.EffectiveTopTube | 566.7 | 589 | 613.3 | 641.9 | 668.5 |
| B.StandOver | 688.6 | 708.3 | 747.2 | 779.1 | 808.7 |
| C.Reach | 400.6 | 421.5 | 444.4 | 470.4 | 494.3 |
| D.Stack | 601.9 | 606.4 | 611 | 620.1 | 629.3 |
| E.TotalSeatTubeLength | 355 | 381 | 431 | 470 | 508 |
| F.HeadtubeLength | 95 | 100 | 105 | 115 | 125 |
| G.HeadtubeAngle | 68.6 | 68.6 | 68.6 | 68.5 | 68.5 |
| H.SeatTubeAngle | 74.6 | 74.6 | 74.6 | 74.5 | 74.5 |
| I.BBDrop | 62 | 62 | 61.9 | 61.8 | 61.7 |
| K.ChainstayLength | 439 | 439 | 439 | 439 | 439 |
| L.ForkLengthAxletoCrown | 501 | 501 | 501 | 501 | 501 |
| M.ForkOffset | 51 | 51 | 51 | 51 | 51 |
| N.Wheelbase | 1101.9 | 1124.7 | 1149.6 | 1179.4 | 1207.1 |
| CrankArmLength | 170 | 170 | 175 | 175 | 175 |
| HandlebarWidth | 750mm | 750mm | 800mm | 800mm | 800mm |
| RecommendedRiderHeight | 157cm-168cm | 160cm-175cm | 173cm-183cm | 180cm-191cm | 188cm-UP |
| StemLength | 60 | 60 | 60 | 60 | 60 |

Measurements based on

- OE spec 120mm 29/27.5+ suspension fork at 25% sag 27.5 x 2.8" tire measuring 722mm in diameter
- Standover is measured from vertically from ground to the top of the toptube, 50mm forward of the BB. Add 8-12.5mm (0.3-0.5") for 29 x 2.4-2.6" wheels/tires