



Geometry Chart

Size	XS	SM	MD	LG	XL
A.EffectiveTopTube	566.7	589	613.3	641.9	668.5
B.StandOver	688.6	708.3	747.2	779.1	808.7
C.Reach	400.6	421.5	444.4	470.4	494.3
D.Stack	601.9	606.4	611	620.1	629.3
E.TotalSeatTubeLength	355	381	431	470	508
F.HeadtubeLength	95	100	105	115	125
G.HeadtubeAngle	68.6	68.6	68.6	68.5	68.5
H.SeatTubeAngle	74.6	74.6	74.6	74.5	74.5
I.BBDrop	62	62	61.9	61.8	61.7
K.ChainstayLength	439	439	439	439	439
L.ForkLengthAxletoCrown	501	501	501	501	501
M.ForkOffset	51	51	51	51	51
N.Wheelbase	1101.9	1124.7	1149.6	1179.4	1207.1
CrankArmLength	170	170	175	175	175
HandlebarWidth	750mm	750mm	800mm	800mm	800mm
RecommendedRiderHeight	157cm-168cm	160cm-175cm	173cm-183cm	180cm-191cm	188cm-UP
StemLength	60	60	60	60	60

Measurements based on

- OE spec 120mm 29/27.5+ suspension fork at 25% sag 27.5 x 2.8" tire measuring 722mm in diameter
- Standover is measured from vertically from ground to the top of the toptube, 50mm forward of the BB. Add 8-12.5mm (0.3-0.5") for 29 x 2.4-2.6" wheels/tires