



### Geometry Chart

Size	XS	SM	MD	LG	XL
<b>A.EffectiveTopTube</b>	568.2	590.5	614.8	643.5	670.1
<b>B.StandOver</b>	678.6	698.3	737.2	769.1	798.7
<b>C.Reach</b>	395	416	439	465	489
<b>D.Stack</b>	605.6	610.2	614.9	624.2	633.4
<b>E.TotalSeatTubeLength</b>	355	381	431	470	508
<b>F.HeadtubeLength</b>	95	100	105	115	125
<b>G.HeadtubeAngle</b>	68	68	68	68	68
<b>H.SeatTubeAngle</b>	74	74	74	74	74
<b>I.BBDrop</b>	58	58	58	58	58
<b>K.ChainstayLength</b>	439	439	439	439	439
<b>L.ForkLengthAxletoCrown</b>	510	510	510	510	510
<b>M.ForkOffset</b>	46	46	46	46	46
<b>N.Wheelbase</b>	1100.6	1123.4	1148.3	1178	1205.8
<b>CrankArmLength</b>	170	170	175	175	175
<b>HandlebarWidth</b>	750mm	750mm	800mm	800mm	800mm
<b>RecommendedRiderHeight</b>	157cm-168cm	160cm-175cm	173cm-183cm	180cm-191cm	188cm-UP
<b>StemLength</b>	60	60	60	60	60

### Measurements based on

- OE spec 120mm 29/27.5+ suspension fork at 25% sag 27.5 x 2.8" tire measuring 722mm in diameter
- Standover is measured from vertically from ground to the top of the toptube, 50mm forward of the BB. Add 8-12.5mm (0.3-0.5") for 29 x 2.4-2.6" wheels/tires