



**Geometry Chart**

Size	XS- 150mmFork	SM- 150mmFork	MD- 150mmFork	LG- 150mmFork	XL- 150mmFork	XS- 140mmFork	SM- 140mmFork	MD- 140mmFork	LG- 140mmFork	XL- 140mmFork
<b>A.EffectiveTopTube</b>	563/562	595/594	616/615	638/637	659/658	562/561	593/592	615/614	636/635	658/657
<b>B.StandOver</b>	704/706	7012/714	7012/714	712/714	713/716	700/702	708/711	708/711	708/711	708/711
<b>C.Reach</b>	391/393	420/423	439/441	458/460	476/479	396/398	424/427	443/446	462/465	481/484
<b>D.Stack</b>	584/582	593/591	602/600	611/610	621/619	580/579	590/588	599/597	608/606	617/615
<b>E.TotalSeatTubeLength</b>	368	406	432	470	508	368	406	432	470	508
<b>F.HeadtubeLength</b>	100	110	120	130	140	100	110	120	130	140
<b>G.HeadtubeAngle</b>	65.8/66.1	65.8/66.1	65.8/66.1	65.8/66.1	65.8/66.1	66.3/66.5	66.3/66.5	66.3/66.5	66.3/66.5	66.3/66.5
<b>H.SeatTubeAngle</b>	73.6/74.0	73.6/74.0	73.6/74.0	73.6/74.0	73.6/74.0	74.1/74.3	74.1/74.3	74.1/74.3	74.1/74.3	74.1/74.3
<b>I.BBDrop</b>	12.6/10	12.6/10	12.6/10	12.6/10	12.6/10	16/12.8	16/12.8	16/12.8	16/12.8	16/12.8
<b>K.ChainstayLength</b>	426/425	426/425	426/425	426/425	426/425	426/425	426/425	426/425	426/425	426/425
<b>L.ForkLengthAxletoCrown</b>	542	542	542	542	542	532	532	532	532	532
<b>M.ForkOffset</b>	37	37	37	37	37	37	37	37	37	37
<b>N.Wheelbase</b>	1114/1113	1147/1146	1170/1169	1193/1192	1216/1215	1110/1109	1143/1142	1166/1165	1189/1188	1212/1211
<b>CrankArmLength</b>	165	170	170	175	175	165	170	170	175	175
<b>HandlebarWidth</b>	760mm	760mm	800mm	800mm	800mm	760mm	760mm	800mm	800mm	800mm
<b>RecommendedRiderHeight</b>	155cm- 168cm	168cm- 175cm	175cm- 183cm	183cm- 190cm	190cm-UP	155cm- 168cm	168cm- 175cm	175cm- 183cm	183cm- 190cm	190cm-UP
<b>StemLength</b>	50	50	50	50	50	50	50	50	50	50

**Measurements based on**

- An unsprung bike (no sag) 150mm chart reflects measurement with an average 150mm 27.5 suspension fork; 140mm chart reflects measurement with an average 140mm 27.5 suspension fork. A 27.5 x 2.6" tire measuring 717mm in diameter
- Standover is measured 50mm in front of bottom bracket
- Note: Where two measurements are listed, the first number is with Flip Chip in Low position; the second number is with Flip Chip in High position