



Geometry Chart

| Size | SM | MD | LG | XL |
|--------------------------------|-------------|-------------|-------------|-----------|
| A.EffectiveTopTube | 593/592 | 615/614 | 636/636 | 658/657 |
| B.StandOver | 733/736 | 744/746 | 755/758 | 765/768 |
| C.Reach | 421/425 | 441/443 | 460/462 | 479/481 |
| D.Stack | 610/608 | 619/617 | 628/626 | 637/636 |
| E.TotalSeatTubeLength | 419 | 444 | 483 | 520 |
| F.HeadtubeLength | 103 | 113 | 123 | 133 |
| G.HeadtubeAngle | 67.8/68.0 | 67.8/68.0 | 67.8/68.0 | 67.8/68.0 |
| H.SeatTubeAngle | 74.3/74.6 | 74.3/74.6 | 74.3/74.6 | 74.3/74.6 |
| I.BBDrop | 39/36 | 39/36 | 39/36 | 39/36 |
| K.ChainstayLength | 432/431 | 432/431 | 432/431 | 432/431 |
| L.ForkLengthAxletoCrown | 531 | 531 | 531 | 531 |
| M.ForkOffset | 44 | 44 | 44 | 44 |
| N.Wheelbase | 1131 | 1154 | 1176 | 1199 |
| CrankArmLength | 165 | 170 | 170 | 175 |
| HandlebarWidth | 800 | 800 | 800 | 800 |
| RecommendedRiderHeight | 165cm-173cm | 173cm-180cm | 180cm-188cm | 188cm-UP |
| StemLength | 50 | 50 | 50 | 50 |

Measurements based on

- An unsprung bike (no sag)A 29 x 2.35" tire measuring 744mm in diameter
- Standover is measured from vertically from ground to bend in top tube, subtract 2-8mm (0.1-0.3") for 27.5 x 2.8-3.0" tires
- Measurements shown are for LOW / HIGH Flip Chip settings