



Geometry Chart

Size	SM	MD	LG	XL
A.EffectiveTopTube	593/592	615/614	636/636	658/657
B.StandOver	733/736	744/746	755/758	765/768
C.Reach	421/425	441/443	460/462	479/481
D.Stack	610/608	619/617	628/626	637/636
E.TotalSeatTubeLength	419	444	483	520
F.HeadtubeLength	103	113	123	133
G.HeadtubeAngle	67.8/68.0	67.8/68.0	67.8/68.0	67.8/68.0
H.SeatTubeAngle	74.3/74.6	74.3/74.6	74.3/74.6	74.3/74.6
I.BBDrop	39/36	39/36	39/36	39/36
K.ChainstayLength	432/431	432/431	432/431	432/431
L.ForkLengthAxletoCrown	531	531	531	531
M.ForkOffset	44	44	44	44
N.Wheelbase	1131	1154	1176	1199
CrankArmLength	165	170	170	175
HandlebarWidth	760	760	760	760
RecommendedRiderHeight	165cm-173cm	173cm-180cm	180cm-188cm	188cm-UP
StemLength	50	50	50	50

Measurements based on

- An unsprung bike (no sag) A 29 x 2.35" tire measuring 744mm in diameter
- Standover is measured from vertically from ground to bend in top tube, subtract 2-8mm (0.1-0.3") for 27.5 x 2.8-3.0" tires
- Measurements shown are for LOW / HIGH Flip Chip settings