



Geometry Chart (INCHES)

		XS/49	S/52	M/54	L/56	XL/58
A	head tube angle	71.0 °	72.0 °	72.5 °	73.0 °	73.3 °
B	head tube length	4.1 in	4.9 in	5.7 in	6.5 in	7.3 in
C	top tube horizontal	20.3 in	20.9 in	21.5 in	22.0 in	22.6 in
D	standover height (TT center)	29.6 in	30.6 in	31.5 in	32.4 in	33.2 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	11.0 in	11.0 in	11.0 in	11.0 in	11.0 in
G	wheel base	39.2 in	39.3 in	39.5 in	39.7 in	40.0 in
H	BB center to toptube center	17.1 in	18.1 in	19.1 in	20.1 in	21.1 in
I	BB center to top of seattube	19.3 in	20.5 in	21.3 in	22.0 in	22.8 in
J	seat angle	75.0 °	74.5 °	74.0 °	73.5 °	73.1 °
K	chainstay	16.6 in	16.6 in	16.6 in	16.6 in	16.6 in
L	reach	14.7 in	14.8 in	15.0 in	15.1 in	15.3 in
M	stack	20.8 in	21.7 in	22.5 in	23.4 in	24.2 in
N	stem length	3.5 in	3.9 in	4.3 in	4.7 in	4.7 in
O	trail					

Geometry Chart (INCHES)

		XS/49	S/52	M/54	L/56	XL/58
A	head tube angle	71.0 °	72.0 °	72.5 °	73.0 °	73.3 °
B	head tube length	4.1 in	4.9 in	5.7 in	6.5 in	7.3 in
C	top tube horizontal	20.3 in	20.9 in	21.5 in	22.0 in	22.6 in
D	standover height (TT center)	29.6 in	30.6 in	31.5 in	32.4 in	33.2 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	11.0 in	11.0 in	11.0 in	11.0 in	11.0 in
G	wheel base	39.2 in	39.3 in	39.5 in	39.7 in	40.0 in
H	BB center to toptube center	17.1 in	18.1 in	19.1 in	20.1 in	21.1 in
I	BB center to top of seattube	19.3 in	20.5 in	21.3 in	22.0 in	22.8 in
J	seat angle	75.0 °	74.5 °	74.0 °	73.5 °	73.1 °
K	chainstay	16.6 in	16.6 in	16.6 in	16.6 in	16.6 in
L	reach	14.7 in	14.8 in	15.0 in	15.1 in	15.3 in
M	stack	20.8 in	21.7 in	22.5 in	23.4 in	24.2 in
N	stem length	3.5 in	3.9 in	4.3 in	4.7 in	4.7 in

