



### Geometry Chart (INCHES)

		<b>XS/49</b>	<b>S/52</b>	<b>M/54</b>	<b>L/56</b>	<b>XL/58</b>
A	head tube angle	70.0 °	70.0 °	71.0 °	71.0 °	71.0 °
B	head tube length	3.7 in	4.8 in	5.5 in	6.5 in	7.4 in
C	top tube horizontal	20.4 in	21.0 in	21.8 in	22.8 in	23.3 in
D	standover height	29.9 in	30.9 in	31.8 in	32.6 in	33.3 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	11.1 in	11.1 in	11.1 in	11.1 in	11.1 in
G	wheel base	39.7 in	40.3 in	40.5 in	41.3 in	41.9 in
H	BB center to toptube center	17.6 in	18.8 in	19.6 in	20.3 in	21.1 in
I	BB center to top of seattube	18.8 in	20.0 in	20.8 in	21.5 in	22.3 in
J	seat angle	74.5 °	74.0 °	73.5 °	73.0 °	73.0 °
K	chainstay	16.7 in	16.7 in	16.7 in	16.7 in	16.7 in
L	reach	14.7 in	14.9 in	15.2 in	15.7 in	16.0 in
M	stack	20.4 in	21.4 in	22.3 in	23.2 in	24.0 in
N	stem length	3.3 in	3.7 in	4.1 in	4.1 in	4.4 in

### Geometry Chart (MM)

		<b>XS/49</b>	<b>S/52</b>	<b>M/54</b>	<b>L/56</b>	<b>XL/58</b>
A	head tube angle	70.0 °	70.0 °	71.0 °	71.0 °	71.0 °
B	head tube length	95.0 mm	122.0 mm	140.0 mm	166.0 mm	187.0 mm
C	top tube horizontal	518.0 mm	534.5 mm	554.5 mm	578.5 mm	592.5 mm
D	standover height	759.0 mm	786.0 mm	807.0 mm	828.0 mm	847.0 mm
E	BB offset	-71.0 mm	-71.0 mm	-71.0 mm	-71.0 mm	-71.0 mm
F	BB height	283.0 mm	283.0 mm	283.0 mm	283.0 mm	283.0 mm
G	wheel base	1,009.4 mm	1,022.9 mm	1,029.2 mm	1,048.7 mm	1,063.5 mm
H	BB center to toptube center	447.0 mm	477.0 mm	498.0 mm	516.0 mm	536.0 mm
I	BB center to top of seattube	477.0 mm	507.0 mm	528.0 mm	546.0 mm	566.0 mm
J	seat angle	74.5 °	74.0 °	73.5 °	73.0 °	73.0 °
K	chainstay	425.0 mm	425.0 mm	425.0 mm	425.0 mm	425.0 mm
L	reach	374.1 mm	378.4 mm	387.1 mm	398.2 mm	406.1 mm
M	stack	519.0 mm	544.4 mm	565.3 mm	589.9 mm	609.7 mm
N	stem length	83.0 mm	93.0 mm	103.0 mm	103.0 mm	113.0 mm