



Geometry Chart (INCHES)

		XS/49	S/52	M/54	L/56	XL/58
A	head tube angle	70.0 °	70.0 °	71.0 °	71.0 °	71.0 °
B	head tube length	3.7 in	4.8 in	5.5 in	6.5 in	7.4 in
C	top tube horizontal	20.4 in	21.0 in	21.8 in	22.8 in	23.3 in
D	standover height	29.9 in	30.9 in	31.8 in	32.6 in	33.3 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	11.1 in	11.1 in	11.1 in	11.1 in	11.1 in
G	wheel base	39.7 in	40.3 in	40.5 in	41.3 in	41.9 in
H	BB center to toptube center	17.6 in	18.8 in	19.6 in	20.3 in	21.1 in
I	BB center to top of seattube	18.8 in	20.0 in	20.8 in	21.5 in	22.3 in
J	seat angle	74.5 °	74.0 °	73.5 °	73.0 °	73.0 °
K	chainstay	16.7 in	16.7 in	16.7 in	16.7 in	16.7 in
L	reach	14.7 in	14.9 in	15.2 in	15.7 in	16.0 in
M	stack	20.4 in	21.4 in	22.3 in	23.2 in	24.0 in
N	stem length	3.3 in	3.7 in	4.1 in	4.1 in	4.4 in

Geometry Chart (INCHES)

		XS/49	S/52	M/54	L/56	XL/58
A	head tube angle	70.0 °	70.0 °	71.0 °	71.0 °	71.0 °
B	head tube length	3.7 in	4.8 in	5.5 in	6.5 in	7.4 in
C	top tube horizontal	20.4 in	21.0 in	21.8 in	22.8 in	23.3 in
D	standover height	29.9 in	30.9 in	31.8 in	32.6 in	33.3 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	11.1 in	11.1 in	11.1 in	11.1 in	11.1 in
G	wheel base	39.7 in	40.3 in	40.5 in	41.3 in	41.9 in
H	BB center to toptube center	17.6 in	18.8 in	19.6 in	20.3 in	21.1 in
I	BB center to top of seattube	18.8 in	20.0 in	20.8 in	21.5 in	22.3 in
J	seat angle	74.5 °	74.0 °	73.5 °	73.0 °	73.0 °
K	chainstay	16.7 in	16.7 in	16.7 in	16.7 in	16.7 in
L	reach	14.7 in	14.9 in	15.2 in	15.7 in	16.0 in
M	stack	20.4 in	21.4 in	22.3 in	23.2 in	24.0 in
N	stem length	3.3 in	3.7 in	4.1 in	4.1 in	4.4 in