



**Geometry Chart (INCHES)**

		<b>XS/49</b>	<b>S/52</b>	<b>M/54</b>	<b>L/56</b>	<b>XL/58</b>
A	head tube angle	71.0 °	72.0 °	72.5 °	73.0 °	73.3 °
B	head tube length	4.1 in	4.9 in	5.7 in	6.5 in	7.3 in
C	top tube horizontal	20.3 in	20.9 in	21.5 in	22.0 in	22.6 in
D	standover height (TT center)	29.6 in	30.6 in	31.5 in	32.4 in	33.2 in
E	BB offset	-2.8 in	-2.8 in	-2.8 in	-2.8 in	-2.8 in
F	BB height	11.0 in	11.0 in	11.0 in	11.0 in	11.0 in
G	wheel base	39.2 in	39.3 in	39.5 in	39.7 in	40.0 in
H	BB center to toptube center	17.1 in	18.1 in	19.1 in	20.1 in	21.1 in
I	BB center to top of seattube	19.3 in	20.5 in	21.3 in	22.0 in	22.8 in
J	seat angle	75.0 °	74.5 °	74.0 °	73.5 °	73.1 °
K	chainstay	16.6 in	16.6 in	16.6 in	16.6 in	16.6 in
L	reach	14.7 in	14.8 in	15.0 in	15.1 in	15.3 in
M	stack	20.8 in	21.7 in	22.5 in	23.4 in	24.2 in
N	stem length	3.5 in	3.9 in	4.3 in	4.7 in	4.7 in
0	trail					

**Geometry Chart (MM)**

		<b>XS/49</b>	<b>S/52</b>	<b>M/54</b>	<b>L/56</b>	<b>XL/58</b>
A	head tube angle	71.0 °	72.0 °	72.5 °	73.0 °	73.3 °
B	head tube length	105.0 mm	125.0 mm	145.0 mm	165.0 mm	185.0 mm
C	top tube horizontal	515.0 mm	530.0 mm	545.0 mm	560.0 mm	575.0 mm
D	standover height (TT center)	752.0 mm	776.0 mm	799.0 mm	822.0 mm	843.0 mm
E	BB offset	-70.0 mm	-70.0 mm	-70.0 mm	-70.0 mm	-70.0 mm
F	BB height	279.0 mm	279.0 mm	279.0 mm	279.0 mm	279.0 mm
G	wheel base	995.1 mm	997.0 mm	1,002.6 mm	1,007.5 mm	1,014.8 mm
H	BB center to toptube center	435.0 mm	460.0 mm	485.0 mm	510.0 mm	535.0 mm
I	BB center to top of seattube	490.0 mm	520.0 mm	540.0 mm	560.0 mm	580.0 mm
J	seat angle	75.0 °	74.5 °	74.0 °	73.5 °	73.1 °
K	chainstay	422.0 mm	422.0 mm	422.0 mm	422.0 mm	422.0 mm
L	reach	373.2 mm	377.0 mm	380.9 mm	384.3 mm	388.6 mm
M	stack	529.1 mm	551.6 mm	572.4 mm	593.3 mm	613.6 mm
N	stem length	90.0 mm	100.0 mm	110.0 mm	120.0 mm	120.0 mm

0	trail
---	-------