



ASPECT

Geometry Chart (INCHES)

		XS	S	M	L	XL	XXL
A	head tube angle	68.5 °	68.5 °	68.5 °	68.5 °	68.5 °	68.5 °
B	head tube length	3.7 in	3.9 in	4.3 in	4.7 in	5.3 in	5.9 in
C	top tube horizontal	22.0 in	23.0 in	23.6 in	24.2 in	25.0 in	25.8 in
D	standover height	29.3 in	30.4 in	30.8 in	32.3 in	33.7 in	35.1 in
E	BB offset	-2.4 in	-2.4 in	-2.4 in	-2.4 in	-2.4 in	-2.4 in
F	BB height	12.4 in	12.4 in	12.4 in	12.4 in	12.4 in	12.4 in
G	wheel base	43.4 in	42.9 in	43.4 in	44.2 in	45.0 in	45.8 in
H	BB center to toptube center	12.2 in	13.7 in	15.5 in	17.1 in	19.1 in	21.0 in
I	BB center to top of seattube	14.0 in	15.6 in	17.3 in	18.9 in	20.9 in	22.8 in
J	seat angle	73.5 °	73.5 °	73.5 °	73.5 °	73.5 °	73.5 °
K	chainstay	17.7 in	17.7 in	17.7 in	17.7 in	17.7 in	17.7 in
L	reach	15.3 in	16.0 in	16.5 in	17.0 in	17.6 in	18.2 in
M	stack	22.8 in	23.7 in	24.1 in	24.5 in	25.0 in	25.6 in
N	stem length	2.0 in	2.4 in	2.8 in	3.1 in	3.5 in	3.9 in

Geometry Chart (MM)

		XS	S	M	L	XL	XXL
A	head tube angle	68.5 °	68.5 °	68.5 °	68.5 °	68.5 °	68.5 °
B	head tube length	95.0 mm	100.0 mm	110.0 mm	120.0 mm	135.0 mm	150.0 mm
C	top tube horizontal	560.0 mm	585.0 mm	600.0 mm	615.0 mm	635.0 mm	655.0 mm
D	standover height	743.0 mm	771.0 mm	783.0 mm	821.0 mm	857.0 mm	891.0 mm
E	BB offset	-60.0 mm	-60.0 mm	-60.0 mm	-60.0 mm	-60.0 mm	-60.0 mm
F	BB height	316.0 mm	316.0 mm	316.0 mm	316.0 mm	316.0 mm	316.0 mm
G	wheel base	1,102.0 mm	1,090.0 mm	1,102.0 mm	1,123.0 mm	1,144.0 mm	1,164.0 mm
H	BB center to toptube center	309.0 mm	349.0 mm	394.0 mm	434.0 mm	484.0 mm	534.0 mm
I	BB center to top of seattube	355.0 mm	395.0 mm	440.0 mm	480.0 mm	530.0 mm	580.0 mm
J	seat angle	73.5 °	73.5 °	73.5 °	73.5 °	73.5 °	73.5 °
K	chainstay	450.0 mm	450.0 mm	450.0 mm	450.0 mm	450.0 mm	450.0 mm
L	reach	388.0 mm	406.0 mm	419.0 mm	431.0 mm	447.0 mm	463.0 mm
M	stack	580.0 mm	603.0 mm	612.0 mm	622.0 mm	636.0 mm	649.0 mm
N	stem length	50.0 mm	60.0 mm	70.0 mm	80.0 mm	90.0 mm	100.0 mm