



ASPECT eRIDE

Geometry Chart (INCHES)

		S / 900	M / 900	L / 900	XL / 900
A	head tube angle	67.5 °	67.5 °	67.5 °	67.5 °
B	head tube length	4.3 in	4.7 in	5.1 in	5.5 in
C	top tube horizontal	22.8 in	23.6 in	24.4 in	25.2 in
D	standover height	31.0 in	31.9 in	33.0 in	33.6 in
E	BB offset	2.2 in	2.2 in	2.2 in	2.2 in
F	BB height	12.6 in	12.6 in	12.6 in	12.6 in
G	wheel base	45.7 in	46.5 in	47.3 in	48.1 in
H	BB center to toptube center				
I	BB center to top of seat tube	15.7 in	17.3 in	18.9 in	20.5 in
J	Effective seat angle GEN3	75.2 °	75.0 °	74.9 °	74.7 °
K	chainstay	18.9 in	18.9 in	18.9 in	18.9 in
L	reach	15.7 in	16.3 in	17.0 in	17.7 in
M	stack	25.1 in	25.4 in	25.7 in	26.1 in
N	stem length				
O	trail	3.6 in	3.8 in	3.8 in	3.8 in

Geometry Chart (MM)

		S / 900	M / 900	L / 900	XL / 900
A	head tube angle	67.5 °	67.5 °	67.5 °	67.5 °
B	head tube length	110.0 mm	120.0 mm	130.0 mm	140.0 mm
C	top tube horizontal	580.0 mm	600.0 mm	620.0 mm	640.0 mm
D	standover height	787.0 mm	809.0 mm	838.0 mm	853.0 mm
E	BB offset	57.0 mm	57.0 mm	57.0 mm	57.0 mm
F	BB height	320.0 mm	320.0 mm	320.0 mm	320.0 mm
G	wheel base	1,160.0 mm	1,180.0 mm	1,202.0 mm	1,222.0 mm
H	BB center to toptube center				
I	BB center to top of seat tube	400.0 mm	440.0 mm	480.0 mm	520.0 mm
J	Effective seat angle GEN3	75.2 °	75.0 °	74.9 °	74.7 °
K	chainstay	480.0 mm	480.0 mm	480.0 mm	480.0 mm
L	reach	398.0 mm	415.0 mm	433.0 mm	450.0 mm
M	stack	637.0 mm	644.0 mm	653.0 mm	663.0 mm
N	stem length				

0	trail	90.5 mm	97.0 mm	97.0 mm	97.0 mm
---	-------	---------	---------	---------	---------