



Geometry Chart (INCHES)

		XS / 700	S / 700	M / 900	L / 900
A	head tube angle	68.0 °	68.0 °	68.5 °	68.5 °
B	head tube length	3.7 in	3.9 in	4.3 in	4.7 in
C	top tube horizontal	22.0 in	23.0 in	23.6 in	24.2 in
D	standover height	26.7 in	27.7 in	29.5 in	30.6 in
E	BB offset	-1.7 in	-1.7 in	-2.4 in	-2.4 in
F	BB height	12.1 in	12.1 in	12.4 in	12.4 in
G	wheel base	42.8 in	43.9 in	43.4 in	44.2 in
H	BB center to toptube center	12.2 in	13.4 in	15.4 in	17.0 in
I	BB center to top of seattube	14.0 in	15.6 in	17.3 in	18.9 in
J	seat angle	74.0 °	74.0 °	73.5 °	73.5 °
K	chainstay	17.1 in	17.1 in	17.7 in	17.7 in
L	reach	15.8 in	16.5 in	16.5 in	17.0 in
M	stack	21.7 in	22.6 in	24.1 in	24.5 in
N	stem length	2.0 in	2.0 in	2.4 in	2.4 in

Geometry Chart (MM)

		XS / 700	S / 700	M / 900	L / 900
A	HEAD TUBE ANGLE	68.0 °	68.0 °	68.5 °	68.5 °
B	HEAD TUBE LENGTH	95.0 MM	100.0 MM	110.0 MM	120.0 MM
C	TOP TUBE HORIZONTAL	560.0 MM	585.0 MM	600.0 MM	615.0 MM
D	STANDOVER HEIGHT	678.0 MM	704.0 MM	750.0 MM	777.0 MM
E	BB OFFSET	-44.0 MM	-44.0 MM	-60.0 MM	-60.0 MM
F	BB HEIGHT	308.5 MM	308.5 MM	316.0 MM	316.0 MM
G	WHEEL BASE	1,087.0 MM	1,115.0 MM	1,102.0 MM	1,123.0 MM
H	BB CENTER TO TOPTUBE CENTER	311.0 MM	341.0 MM	391.0 MM	431.0 MM
I	BB CENTER TO TOP OF SEATTUBE	355.0 MM	395.0 MM	440.0 MM	480.0 MM
J	SEAT ANGLE	74.0 °	74.0 °	73.5 °	73.5 °
K	CHAINSTAY	435.0 MM	435.0 MM	450.0 MM	450.0 MM
L	REACH	402.0 MM	420.0 MM	419.0 MM	431.0 MM
M	STACK	552.0 MM	575.0 MM	612.0 MM	622.0 MM
N	STEM LENGTH	50.0 MM	50.0 MM	60.0 MM	60.0 MM