



Geometry Chart (INCHES)

| | | XS/49 | S/52 | M/54 | L/56 |
|---|------------------------------|--------------|-------------|-------------|-------------|
| A | head tube angle | 70.0 ° | 70.0 ° | 71.0 ° | 71.0 ° |
| B | head tube length | 3.7 in | 4.8 in | 5.5 in | 6.5 in |
| C | top tube horizontal | 20.4 in | 21.0 in | 21.8 in | 22.8 in |
| D | standover height | 29.9 in | 30.9 in | 31.8 in | 32.6 in |
| E | BB offset | -2.8 in | -2.8 in | -2.8 in | -2.8 in |
| F | BB height | 11.1 in | 11.1 in | 11.1 in | 11.1 in |
| G | wheel base | 39.7 in | 40.3 in | 40.5 in | 41.3 in |
| H | BB center to toptube center | 17.6 in | 18.8 in | 19.6 in | 20.3 in |
| I | BB center to top of seattube | 18.8 in | 20.0 in | 20.8 in | 21.5 in |
| J | seat angle | 74.5 ° | 74.0 ° | 73.5 ° | 73.0 ° |
| K | chainstay | 16.7 in | 16.7 in | 16.7 in | 16.7 in |
| L | reach | 14.7 in | 14.9 in | 15.2 in | 15.7 in |
| M | stack | 20.4 in | 21.4 in | 22.3 in | 23.2 in |
| N | stem length | 2.9 in | 3.3 in | 3.7 in | 4.1 in |

Geometry Chart (INCHES)

| | | XS/49 | S/52 | M/54 | L/56 |
|---|------------------------------|--------------|-------------|-------------|-------------|
| A | head tube angle | 70.0 ° | 70.0 ° | 71.0 ° | 71.0 ° |
| B | head tube length | 3.7 in | 4.8 in | 5.5 in | 6.5 in |
| C | top tube horizontal | 20.4 in | 21.0 in | 21.8 in | 22.8 in |
| D | standover height | 29.9 in | 30.9 in | 31.8 in | 32.6 in |
| E | BB offset | -2.8 in | -2.8 in | -2.8 in | -2.8 in |
| F | BB height | 11.1 in | 11.1 in | 11.1 in | 11.1 in |
| G | wheel base | 39.7 in | 40.3 in | 40.5 in | 41.3 in |
| H | BB center to toptube center | 17.6 in | 18.8 in | 19.6 in | 20.3 in |
| I | BB center to top of seattube | 18.8 in | 20.0 in | 20.8 in | 21.5 in |
| J | seat angle | 74.5 ° | 74.0 ° | 73.5 ° | 73.0 ° |
| K | chainstay | 16.7 in | 16.7 in | 16.7 in | 16.7 in |
| L | reach | 14.7 in | 14.9 in | 15.2 in | 15.7 in |
| M | stack | 20.4 in | 21.4 in | 22.3 in | 23.2 in |
| N | stem length | 2.9 in | 3.3 in | 3.7 in | 4.1 in |