



Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	63.8 °	63.8 °	63.8 °	63.8 °
B	head tube length	3.7 in	3.9 in	4.5 in	4.9 in
C	top tube horizontal	22.4 in	23.6 in	24.6 in	25.6 in
D	standover height	28.3 in	28.6 in	29.0 in	29.7 in
E	BB offset	-1.0 in	-1.0 in	-1.0 in	-1.0 in
F	BB height	13.8 in	13.8 in	13.8 in	13.8 in
G	wheel base	47.5 in	48.8 in	50.0 in	51.2 in
H	BB center to toptube center				
I	BB center to top of seattube	15.0 in	16.1 in	17.3 in	18.5 in
J	seat angle	77.0 °	77.2 °	77.4 °	77.6 °
K	chainstay	17.3 in	17.3 in	17.3 in	17.3 in
L	reach	16.9 in	18.0 in	19.0 in	20.0 in
M	stack	24.2 in	24.4 in	24.9 in	25.3 in
N	stem length	1.6 in	1.6 in	1.6 in	1.6 in
O	trail	5.3 in	5.3 in	5.3 in	5.3 in
P	Fork length	22.9 in	22.9 in	22.9 in	22.9 in
Q	Maximum Seatpost Insertion	7.3 in	8.4 in	9.6 in	10.8 in
R	Crank Length	6.5 in	6.7 in	6.7 in	6.7 in

Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle	63.8 °	63.8 °	63.8 °	63.8 °
B	head tube length	3.7 in	3.9 in	4.5 in	4.9 in
C	top tube horizontal	22.4 in	23.6 in	24.6 in	25.6 in
D	standover height	28.3 in	28.6 in	29.0 in	29.7 in
E	BB offset	-1.0 in	-1.0 in	-1.0 in	-1.0 in
F	BB height	13.8 in	13.8 in	13.8 in	13.8 in
G	wheel base	47.5 in	48.8 in	50.0 in	51.2 in
H	BB center to toptube center				
I	BB center to top of seattube	15.0 in	16.1 in	17.3 in	18.5 in
J	seat angle	77.0 °	77.2 °	77.4 °	77.6 °
K	chainstay	17.3 in	17.3 in	17.3 in	17.3 in

L	reach	16.9 in	18.0 in	19.0 in	20.0 in
M	stack	24.2 in	24.4 in	24.9 in	25.3 in
N	stem length	1.6 in	1.6 in	1.6 in	1.6 in
O	trail	5.3 in	5.3 in	5.3 in	5.3 in
P	Fork length	22.9 in	22.9 in	22.9 in	22.9 in
Q	Maximum Seatpost Insertion	7.3 in	8.4 in	9.6 in	10.8 in
R	Crank Length	6.5 in	6.7 in	6.7 in	6.7 in