



Geometry Chart (INCHES)

		S	M	L
A	head tube angle	67.2 °	67.2 °	67.2 °
B	head tube length	3.5 in	3.5 in	4.1 in
C	top tube horizontal	22.1 in	23.2 in	24.2 in
D	standover height	29.8 in	30.1 in	30.6 in
E	BB offset	-1.8 in	-1.8 in	-1.8 in
F	BB height	13.0 in	13.0 in	13.0 in
G	wheel base	44.4 in	45.6 in	46.9 in
H	BB center to toptube center			
I	BB center to top of seattube	16.3 in	17.3 in	19.3 in
J	seat angle	75.9 °	76.1 °	76.6 °
K	chainstay	17.2 in	17.2 in	17.2 in
L	reach	16.2 in	17.4 in	18.5 in
M	stack	23.7 in	23.7 in	24.3 in
N	stem length	2.0 in	2.0 in	2.4 in
O	trail	4.5 in	4.5 in	4.5 in
P	Fork Length	20.9 in	20.9 in	20.9 in
Q	Maximum Seatpost Insertion	5.9 in	6.9 in	8.9 in
R	Crank Length	6.7 in	6.7 in	6.9 in

Geometry Chart (INCHES)

		S	M	L
A	head tube angle	67.2 °	67.2 °	67.2 °
B	head tube length	3.5 in	3.5 in	4.1 in
C	top tube horizontal	22.1 in	23.2 in	24.2 in
D	standover height	29.8 in	30.1 in	30.6 in
E	BB offset	-1.8 in	-1.8 in	-1.8 in
F	BB height	13.0 in	13.0 in	13.0 in
G	wheel base	44.4 in	45.6 in	46.9 in
H	BB center to toptube center			
I	BB center to top of seattube	16.3 in	17.3 in	19.3 in
J	seat angle	75.9 °	76.1 °	76.6 °
K	chainstay	17.2 in	17.2 in	17.2 in

L	reach	16.2 in	17.4 in	18.5 in
M	stack	23.7 in	23.7 in	24.3 in
N	stem length	2.0 in	2.0 in	2.4 in
O	trail	4.5 in	4.5 in	4.5 in
P	Fork Length	20.9 in	20.9 in	20.9 in
Q	Maximum Seatpost Insertion	5.9 in	6.9 in	8.9 in
R	Crank Length	6.7 in	6.7 in	6.9 in