



**Geometry Chart (INCHES)**

		S / 900	S / 700	M / 900	M / 700	L / 900	L / 700	XL / 900	XL / 700
LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting		
A	head tube angle	62.9 °	63.2 °	62.9 °	63.2 °	62.9 °	63.2 °	62.9 °	63.2 °
B	head tube length	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in
C	top tube horizontal	21.2 in	21.1 in	22.3 in	22.3 in	24.4 in	24.4 in	25.6 in	25.5 in
D	standover height	28.3 in	28.0 in	28.0 in	27.8 in	28.0 in	27.8 in	27.9 in	27.7 in
E	BB offset	-1.0 in	-0.3 in	-1.0 in	-0.3 in	-1.0 in	-0.3 in	-1.0 in	-0.3 in
F	BB height	13.6 in	13.5 in	13.6 in	13.5 in	13.6 in	13.5 in	13.6 in	13.5 in
G	wheel base	47.5 in	47.7 in	48.7 in	48.9 in	50.0 in	50.1 in	51.1 in	51.3 in
H	BB center to toptube center								
I	BB center to top of seattube	15.9 in	15.9 in	15.9 in	15.9 in	15.9 in	15.9 in	15.9 in	15.9 in
J	seat angle	66.8 °	67.2 °	66.8 °	67.2 °	63.8 °	64.2 °	63.8 °	64.2 °
K	chainstay	17.3 in	17.1 in	17.3 in	17.1 in	17.3 in	17.1 in	17.3 in	17.1 in
L	reach	15.8 in	15.9 in	16.9 in	17.1 in	18.1 in	18.3 in	19.3 in	19.5 in
M	stack	25.0 in	24.9 in	25.0 in	24.9 in	24.9 in	24.9 in	25.0 in	24.9 in
N	stem length	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in
	trail	5.1 in	4.7 in	5.1 in	4.7 in	5.1 in	4.7 in	5.1 in	4.7 in

**Geometry Chart (INCHES)**

		S / 900	S / 700	M / 900	M / 700	L / 900	L / 700	XL / 900	XL / 700
LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting	LOW BB Setting	HIGH BB Setting		

A	head tube angle	62.9 °	63.2 °	62.9 °	63.2 °	62.9 °	63.2 °	62.9 °	63.2 °
B	head tube length	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in
C	top tube horizontal	21.2 in	21.1 in	22.3 in	22.3 in	24.4 in	24.4 in	25.6 in	25.5 in
D	standover height	28.3 in	28.0 in	28.0 in	27.8 in	28.0 in	27.8 in	27.9 in	27.7 in
E	BB offset	-1.0 in	-0.3 in	-1.0 in	-0.3 in	-1.0 in	-0.3 in	-1.0 in	-0.3 in
F	BB height	13.6 in	13.5 in	13.6 in	13.5 in	13.6 in	13.5 in	13.6 in	13.5 in
G	wheel base	47.5 in	47.7 in	48.7 in	48.9 in	50.0 in	50.1 in	51.1 in	51.3 in
H	BB center to toptube center								
I	BB center to top of seattube	15.9 in	15.9 in	15.9 in	15.9 in	15.9 in	15.9 in	15.9 in	15.9 in
J	seat angle	66.8 °	67.2 °	66.8 °	67.2 °	63.8 °	64.2 °	63.8 °	64.2 °
K	chainstay	17.3 in	17.1 in	17.3 in	17.1 in	17.3 in	17.1 in	17.3 in	17.1 in
L	reach	15.8 in	15.9 in	16.9 in	17.1 in	18.1 in	18.3 in	19.3 in	19.5 in
M	stack	25.0 in	24.9 in	25.0 in	24.9 in	24.9 in	24.9 in	25.0 in	24.9 in
N	stem length	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in	2.0 in
trail	5.1 in	4.7 in	5.1 in	4.7 in	5.1 in	4.7 in	5.1 in	4.7 in	