



Geometry Chart (INCHES)

		S	M	L	XL
A	head tube angle (+0.6° Headset Setting)	65.1 °	65.1 °	65.1 °	65.1 °
B	head tube length	3.5 in	3.9 in	4.7 in	5.3 in
C	top tube horizontal	22.4 in	23.7 in	24.9 in	26.0 in
D	standover height	28.7 in	29.1 in	29.7 in	30.3 in
E	BB offset	-1.3 in	-1.3 in	-1.3 in	-1.3 in
F	BB height	13.5 in	13.5 in	13.5 in	13.5 in
G	wheel base	46.5 in	47.9 in	49.2 in	50.4 in
H	BB center to toptube center				
I	BB center to top of seattube	15.0 in	16.1 in	17.3 in	18.5 in
J	seat angle	76.8 °	77.1 °	77.2 °	77.4 °
K	chainstay	17.3 in	17.3 in	17.3 in	17.3 in
L	reach	16.9 in	18.1 in	19.1 in	20.1 in
M	stack	24.3 in	24.6 in	25.4 in	25.9 in
N	stem length	1.6 in	1.6 in	2.0 in	2.0 in
O	trail	5.0 in	5.0 in	5.0 in	5.0 in
P	Fork length	22.5 in	22.5 in	22.5 in	22.5 in
Q	Maximum Seatpost Insertion	6.8 in	8.0 in	9.2 in	10.4 in
R	Crank Length	6.7 in	6.9 in	6.9 in	6.9 in

Geometry Chart (MM)

		S	M	L	XL
A	head tube angle (+0.6° Headset Setting)	65.1 °	65.1 °	65.1 °	65.1 °
B	head tube length	90.0 mm	100.0 mm	120.0 mm	135.0 mm
C	top tube horizontal	570.1 mm	602.2 mm	631.3 mm	659.3 mm
D	standover height	728.5 mm	738.5 mm	753.5 mm	768.5 mm
E	BB offset	-33.0 mm	-33.0 mm	-33.0 mm	-33.0 mm
F	BB height	342.5 mm	342.5 mm	342.5 mm	342.5 mm
G	wheel base	1,182.0 mm	1,216.0 mm	1,249.0 mm	1,281.0 mm
H	BB center to toptube center				
I	BB center to top of seattube	380.0 mm	410.0 mm	440.0 mm	470.0 mm
J	seat angle	76.8 °	77.1 °	77.2 °	77.4 °
K	chainstay	440.0 mm	440.0 mm	440.0 mm	440.0 mm

L	reach	430.0 mm	460.0 mm	485.0 mm	510.0 mm
M	stack	617.0 mm	626.1 mm	644.2 mm	657.8 mm
N	stem length	40.0 mm	40.0 mm	50.0 mm	50.0 mm
O	trail	125.8 mm	125.8 mm	125.8 mm	125.8 mm
P	Fork length	571.0 mm	571.0 mm	571.0 mm	571.0 mm
Q	Maximum Seatpost Insertion	173.0 mm	204.0 mm	234.0 mm	265.0 mm
R	Crank Length	170.0 mm	175.0 mm	175.0 mm	175.0 mm